Lecture 13:

Elimination Algorithm

Sam Roweis

February 27, 2002

Simple Case: Bayes Rule

- For simple models, we can derive the inference formulas by hand using Bayes rule (e.g. responsbility in mixture models).



$$a) \quad p(x,y) = p(x)p(y|x)$$
$$b) \quad p(y|x)$$
$$c) \quad p(x|y) = \frac{p(x)p(y|x)}{\sum_x p(x)p(y|x)}$$

This is called "reversing the arrow".

- In general, the calculation we want to do is:

$$p(\mathbf{x}_F|\mathbf{x}_E) = \frac{\sum_{\mathbf{x}_H} p(\mathbf{x}_E, \mathbf{x}_F, \mathbf{x}_H)}{\sum_{\mathbf{x}_E, \mathbf{x}_H} p(\mathbf{x}_E, \mathbf{x}_F, \mathbf{x}_H)}$$

- Can we do this sums efficiently? Can we avoid repeating unecessary work each time we do inference?
  Yes, if we exploit the factorization of the joint distribution.

Probabilistic Inference

- Partition the random variables in a domain $\mathbf{X}$ into three disjoint subsets, $\mathbf{x}_E$,$\mathbf{x}_F$,$\mathbf{x}_H$. The general *probabilistic inference* problem is to compute the posterior $p(\mathbf{x}_F|\mathbf{x}_E)$ over *query nodes* $\mathbf{x}_F$.
- This involves *conditioning* on *evidence nodes* $\mathbf{x}_E$ and *integrating out marginal nodes* $\mathbf{x}_H$.
- If the joint distribution is represented as a huge table, this is trivial: just select the appropriate indicies in the columns corresponding to $\mathbf{x}_E$ based on the values, sum over the columns corresponding to $\mathbf{x}_H$, and renormalize the resulting table over $\mathbf{x}_F$.
- If the joint is a known continuous function this can often be done as well, using calculus. (e.g. Gaussian: eliminate rows/cols corresponding to $\mathbf{x}_H$; apply conditioning formulas for $p(\mathbf{x}_F|\mathbf{x}_E)$).
- But what if the joint distribution is represented by a directed or undirected graphical model?

Example



The key is to factor and then apply the distributive law.

$$\begin{aligned}
p(\mathbf{x}_1, \bar{\mathbf{x}}_6) &= \sum_{\mathbf{x}_2}\sum_{\mathbf{x}_3}\sum_{\mathbf{x}_4}\sum_{\mathbf{x}_5} p(\mathbf{x}_1)p(\mathbf{x}_2|\mathbf{x}_1)p(\mathbf{x}_3|\mathbf{x}_1)p(\mathbf{x}_4|\mathbf{x}_2)p(\mathbf{x}_5|\mathbf{x}_3)p(\bar{\mathbf{x}}_6|\mathbf{x}_2,\mathbf{x}_3) \\
&= p(\mathbf{x}_1)\sum_{\mathbf{x}_2} p(\mathbf{x}_2|\mathbf{x}_1)\sum_{\mathbf{x}_3} p(\mathbf{x}_3|\mathbf{x}_1)\sum_{\mathbf{x}_4} p(\mathbf{x}_4|\mathbf{x}_2)\sum_{\mathbf{x}_5} p(\mathbf{x}_5|\mathbf{x}_3)p(\bar{\mathbf{x}}_6|\mathbf{x}_2,\mathbf{x}_3) \\
&= p(\mathbf{x}_1)\sum_{\mathbf{x}_2} p(\mathbf{x}_2|\mathbf{x}_1)\sum_{\mathbf{x}_3} p(\mathbf{x}_3|\mathbf{x}_1)\Phi_5(\mathbf{x}_2,\mathbf{x}_3)\sum_{\mathbf{x}_4} p(\mathbf{x}_4|\mathbf{x}_2) \\
&= p(\mathbf{x}_1)\sum_{\mathbf{x}_2} p(\mathbf{x}_2|\mathbf{x}_1)\Phi_4(\mathbf{x}_2)\sum_{\mathbf{x}_3} p(\mathbf{x}_3|\mathbf{x}_1)\Phi_5(\mathbf{x}_2,\mathbf{x}_3) \\
&= p(\mathbf{x}_1)\sum_{\mathbf{x}_2} p(\mathbf{x}_2|\mathbf{x}_1)\Phi_4(\mathbf{x}_2)\Phi_3(\mathbf{x}_1,\mathbf{x}_2) \\
&= p(\mathbf{x}_1)\Phi_2(\mathbf{x}_1)
\end{aligned}$$

Single Node Posteriors

- For a single node posterior (i.e. $\mathbf{x}_F$ is a single node), there is a simple, efficient algorithm based on eliminating nodes.
- Notation: $\bar{\mathbf{x}}_i$ is the value of evidence node $\mathbf{x}_i$.
- The algorithm, called *elimination*, requires a *node ordering* to be given, which tells it which order to do the summations in.
- It also uses a bookeeping trick, called *evidential functions*:

$$g(\bar{\mathbf{x}}_i) = \sum_{\mathbf{x}_i} g(\mathbf{x}_i)\delta(\mathbf{x}_i, \bar{\mathbf{x}}_i)$$

  where $\delta(\mathbf{x}_i, \bar{\mathbf{x}}_i)$ is 1 if $\mathbf{x}_i = \bar{\mathbf{x}}_i$ and 0 otherwise.
- This trick allows us to treat conditioning in the same way as we treat marginalization.

Algorithm Details

- At each step we are trying to marginalize out the next variable in the elimination ordering.
  For marginal nodes this sums them out, for evidence nodes this conditions on their observed values using the evidential functions.
- Each step in Update performs a sum over a product of potential functions. Potentials can be original functions $p(\mathbf{x}_i|\mathbf{x}_{\pi_i})$, evidential functions $\delta(\mathbf{x}_i, \bar{\mathbf{x}}_i)$ or intermediate potentials $\Phi_{\mathbf{x}_i}$.
- The algorithm terminates when we reach the query node, which we put last in the ordering.
- Then we renormalize what we have left and that is the result $p(\mathbf{x}_F|\mathbf{x}_E)$.
- For undirected models, everything is the same except the initialization uses the clique potentials instead of the parent-conditionals.

Elimination Algorithm

Elimination(G, E, F)
  Initialize(G, F)
  Evidence(E)
  Update(G)
  Normalize(F)

Initialize(G, F)
  choose an ordering I such that X_F appears last
  for each node X_i in G
    place $p(x_i \mid x_{\pi_i})$ on the active list
  end

Evidence(E)
  for each node X_i in X_E
    place $\delta(x_i, \bar{x}_i)$ on the active list
  end

Update(G)
  for each X_i in I
    find all potentials from the active list that reference X_i and remove them from the active list
    let ψ_{X_i} be the product of these potentials
    let $\phi_{X_i} = \sum_{x_i} \psi_{X_i}$
    place ϕ_{X_i} on the active list
  end

Normalize(F)
  $p(x_F \mid x_E) \leftarrow \psi_{X_F}(x_F)/\phi_{X_F}$

Marginalization

- Marginalization is a special case of inference.
- To compute the marginal $p(\mathbf{x}_i)$ of a single node, we set it to be the query node and set the evidence set to be empty.
- In directed models, we can ignore all nodes downstream from the query node, and marginalize only the part of the graph before it.
- If the node has no parents, we can read off its marginal directly.
- In undirected models, we need to do the full computation: compute $p(\mathbf{x}_i)/Z$ and then normalize to get Z.
  (We can reuse Z later if we want to save work).

Efficiency Trick

- When working with directed models, sometimes we know that a certain sum will come out to be 1 since it is a conditional probability.
- For example, consider the term $\Phi_4(\mathbf{x}_2)$ in our six node example:

$$\Phi_4(\mathbf{x}_2) = \sum_{\mathbf{x}_4} p(\mathbf{x}_4|\mathbf{x}_2) \equiv 1$$

- We can't use this trick in undirected models, because there are no guarantees about what clique potentials sum to.

Example



Node Elimination

- The algorithm we presented is really a way of eliminating nodes from the graph one by one. For undirected graphs:

```
foreach node x_i in ordering I:
    connect all the neighbours of x_i
    remove x_i from the graph
end
```

- The removal operation requires summing out $\mathbf{x}_i$.
- Summing out $\mathbf{x}_i$ leaves a function involving all its previous neighbours and thus they become connected by this step.
- The original graph, augmented by all the added edges is now a *triangulated* graph.

Added Edges == Triangulation



Moralization

- For directed graphs, the parents may not be explicitly connected, but they are involved in the same potential function $p(\mathbf{x}_i|\mathbf{x}_{\pi_i})$.
- Thus to think of Elimination as a node removal algorithm, we first must connect all the parents of every node and the drop the directions on the links.
- This step is known as "Moralization".