

## Design of Semantics by Abstract Interpretation

Patrick COUSOT  
École Normale Supérieure  
DMI, 45, rue d'Ulm  
75230 Paris cedex 05  
France  
[cousot@dmi.ens.fr](mailto:cousot@dmi.ens.fr)  
<http://www.dmi.ens.fr/~cousot>

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken,  
am Montag, dem 2. Juni 1997 um 14.15 Uhr<sup>1</sup>

<sup>1</sup> Extended version of the invited address at MFPS XIII, CMU, Pittsburgh, March 24, 1997

.../...

- Abstraction of the relational into a **nondeterministic** Plotkin/-Smyth/Hoare **denotational/functional semantics**;
- Abstraction of the natural/demonic relational into a **deterministic denotational/functional semantics**; Scott's semantics;
- Abstraction of nondeterministic denotational semantics to weakest precondition/strongest postcondition **predicate transformer semantics**;
- Abstraction of predicate transformer semantics to à la Hoare **axiomatic semantics**; Program proof methods;
- Extension to the  $\lambda$ -calculus.

## Content

Application of abstract interpretation ideas to the design of formal semantics:

- Examples of abstract interpretations;
- Abstraction of fixpoint semantics;
  - Maximal **trace semantics** of nondeterministic transition systems;
  - Abstraction of the trace into a natural/demonic/angelic **relational semantics**;

.../...

## EXAMPLES OF ABSTRACT INTERPRETATIONS

## Applications of Abstract Interpretation

- Mainly used for specifying *program analyzers* constructively derived from a formal semantics;
- Such analyzers can be used to statically and fully automatically determine *run-time properties of programs*;
- Such run-time information can be used in complement to classical program provers, model-checkers, ... for program *verification* (abstract debugging, ...) and *transformation* (compiler optimization, partial evaluation, parallelization, ...);
- We will show that abstract interpretation can be used to relate and *design program semantics* (and program proof methods).

## Program Analysis by Abstract Interpretation

- (Bit-vector) data flow analysis;
- Strictness analysis and comportment analysis (generalizing strictness, termination, projection and PER analysis);
- Binding time analysis;
- Pointer analysis;
- Set/grammar-based analysis;
- Data dependence analysis (e.g. for vectorization/parallelization);
- Descriptive/soft and prescriptive (polymorphic) typing and type inference;
- Effect systems;
- ...

## Approximation

- The central idea of abstract interpretation <sup>2, 3</sup> is that of *approximation*;
- A *program analyzer* computes a finite approximation of the infinite set of possible run-time behaviors of the program for all possible execution environments (inputs, interrupts, ...);
- A *program semantics* specifies an approximation of the run-time program behaviors in all possible execution environments abstracting away from implementation details.

<sup>2</sup> P. Cousot and R. Cousot. Abstract interpretation: a unified lattice model for static analysis of programs by construction or approximation of fixpoints. In *Conference Record of the Fourth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 238–252, Los Angeles, California, 1977. ACM Press, New York, New York, USA.

<sup>3</sup> P. Cousot and R. Cousot. Systematic design of program analysis frameworks. In *Conference Record of the Sixth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 269–282, San Antonio, Texas, 1979. ACM Press, New York, New York, USA.

## Program Debugging by Abstract Interpretation


- SYNTOX <sup>4, 5</sup> by François Bourdoncle: interval analysis for PASCAL programs;
- For *abstract debugging*, the user can provide:
  - Invariant assertions: `{% ... %}`,
  - Intermittent assertions: `{% ... ? %}` (termination is required by `{% true ? %}` before final `end.`),
- At each program point the analysis provides for each numerical variable `v` a corresponding invariant interval assertion (`v [l..h]`). A star (\*) on one of the bounds (first: `First Condition`, next: `>`, previous: `<`) indicates a *necessary* condition in the form of a run-time check to be inserted in the program for the user assertions to be satisfied. A sharp # indicates a possible overflow.

<sup>4</sup> F. Bourdoncle, *Abstract Debugging of Higher-Order Imperative Languages*, Proc. PLDI'93, ACM Press, 1993, pp. 46-55.  
<sup>5</sup> <http://www.ensmp.fr/bourdonc/syntox.tar.Z>

**File Options Analyze Edit Hide Show**

**File: /users/absint2/cousot/bin/Syntox/programs/MacCarthy0.p**

```
program MacCarthy(input,output); (* MacCarthy's 91-function *)
var x, n : integer;
function HC(n : integer) : integer;
begin
  if (n > 100) then
    HC := n-10
  else begin
    HC := HC(HC(n + 1));
  end;
end;
begin
  read(x);
  n := HC(x);
  writeln(n);
end.
```



**<< First Condition . . . Negation Iterations: - 3 +**

**File Options Analyze Edit Hide Show**

**File: /users/absint2/cousot/bin/Syntox/programs/MacCarthy1.p**

```
program MacCarthy(input,output); (* MacCarthy's 91-function *)
var x, n : integer;
function HC(n : integer) : integer;
begin
  if (n > 100) then
    HC := n-10
  else begin
    HC := HC(HC(n + 1));
  end;
end;
begin
  read(x);
  n := HC(x);
  l := 91 ? ;
(* Intermittent assertion enforcing HC(x) = 91 *)
(* The debugger will determine necessary conditions *)
(* on "x" to ensure that "HC(x) = 91" or "HC" loops *)
end.
```




**<< First Condition . . . Negation Iterations: - 3 +**

**File Options Analyze Edit Hide Show**

**File: /users/absint2/cousot/bin/Syntox/programs/MacCarthy2.p**

```
program MacCarthy(input,output);
(* Generalization of MacCarthy's 91 function *)
var x, n : integer;
function HC(n:integer):integer;
begin
  writeln(n);
  if (n < 100) then
    HC := HC(HC(HC(HC(HC(HC(HC(HC(HC(HC(HC(HC(HC(HC(HC(n + 91)))))))))))))));
  else
    HC := n-10;
end;
begin
  read(x);
  l := 91 ? ;
  n := HC(x);
  writeln(l, n);
end.
```



**<< First Condition . . . Negation Iterations: - 3 +**

```

File Options Analyze Edit Hide Show
File: /users/absint2/cousot/bin/Syntox/programs/MacCarthy3.p

program MacCarthy(input,output);
  /* Generalization of McCarthy's 91 function with error */
var  n: integer;
function MC(n:integer):integer;
begin
  writeln(n);
  if (n < 100) then
    MC := MC(MC(MC(MC(MC(MC(MC(MC(MC(MC(n+90))))))))));
  /* Error ! */
  else
    MC := n+10;
  end;
begin
  read(x);
  n := MC(x);
  writeln('loop ', n);
  if (n= ?) = 1
end.

```


© P. Cousot

13

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997


- Arithmetic congruences<sup>8</sup>:

$$\begin{aligned}x &= 1 \bmod 2 \\ \wedge y &= 0 \bmod 2\end{aligned}$$



- Interval congruences<sup>9</sup>:

$$\begin{aligned}x &\in [0, 2] \bmod 4 \\ \wedge y &= [0, 1] \bmod 3\end{aligned}$$



<sup>8</sup> P. Granger. Static analysis of arithmetical congruences. *Int. J. of Comp. Math.*, 30:165–190, 1989.

<sup>9</sup> F. Masdupuy. Semantic analysis of interval congruences. In D. Björner, M. Broy, and I.V. Pottosin, editors, *Proc. FMPA*, Academgorodok, Novosibirsk, Russia, LNCS 735, pages 142–155. Springer-Verlag, June 28–July 2, 1993.

© P. Cousot

15

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Examples of independent numerical abstractions

- Signs<sup>6</sup>:



- Intervals<sup>7</sup>:

$$\begin{aligned}1 \leq x \leq 5 \\ \wedge 1 \leq y \leq 4\end{aligned}$$



<sup>6</sup> P. Cousot & R. Cousot. Systematic design of program analysis frameworks. In *6<sup>th</sup> POPL*, pages 269–282, San Antonio, Texas, 1979. ACM Press.

<sup>7</sup> P. Cousot and R. Cousot. Static determination of dynamic properties of programs. In *Proc. 2<sup>nd</sup> International Symposium on Programming*, pages 106–130. Dunod, 1976.

© P. Cousot


14

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Examples of relational numerical abstractions


- Linear equalities<sup>10</sup>:

$$-3x + 4y = 1$$



- Simple sections<sup>11</sup>:

$$\begin{aligned}1 \leq x \leq 5 \\ \wedge 1 \leq y \leq 4 \\ \wedge 3 \leq x + y \leq 7\end{aligned}$$



<sup>10</sup> M. Karr. Affine relationships among variables of a program. *Acta Inf.*, 6:133–151, 1976.

<sup>11</sup> V. Balasundaram and K. Kennedy. A technique for summarizing data access and its use in parallelism enhancing transformations. In *SIGPLAN'89 PLDI*, pages 41–53, Portland, Ore., June 21–23, 1989.

© P. Cousot

16

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

- Linear inequalities<sup>12</sup>:

$$\begin{aligned} 3x + y &\geq 7 \\ \wedge \quad 2x + y &\leq 11 \\ \wedge \quad y &\geq 1 \\ \wedge \quad x + 3y &\leq 13 \end{aligned}$$



- Linear congruences<sup>13</sup>:

$$\begin{aligned} 2x + y &\equiv 1 \pmod{2} \\ \wedge \quad y &\equiv 0 \pmod{2} \end{aligned}$$




<sup>12</sup> P. Cousot and N. Halbwachs. Automatic discovery of linear restraints among variables of a program. In *5<sup>th</sup> POPL*, pages 84–97, Tucson, Arizona, 1978. ACM Press.

<sup>13</sup> P. Granger. Static analysis of linear congruence equalities among variables of a program. In S. Abramsky and T.S.E. Maibaum, editors, *TAPSOFT'91; Proc. Int. Joint Conf. on Theory and Practice of Software Development*, Brighton, U.K., Volume 1 (CAAP'91), LNCS 493, pages 169–192. Springer-Verlag, 1991.

## ABSTRACTION OF FIXPOINT SEMANTICS

- Trapezoidal congruences<sup>14, 15</sup>:



<sup>14</sup> F. Masdupuy. Using abstract interpretation to detect array data dependencies. In *Proc. International Symposium on Supercomputing*, pages 19–27, Fukuoka, Japan, Nov. 1991. Kyushu U. Press.

<sup>15</sup> F. Masdupuy. Array operations abstraction using semantic analysis of trapezoid congruences. In *Proc. ACM International Conference on Supercomputing, ICS'92*, pages 226–235, Washington D.C., July 1992.

## Fixpoint Semantics Specification $\langle D, F \rangle$

- $\langle D, \sqsubseteq, \perp, \sqcup \rangle$ 
  - $\langle D, \sqsubseteq \rangle$  Semantic domain poset
  - $\perp$  infimum
  - $\sqcup$  (partially defined) least upper bound
- $F \in D \xrightarrow{\text{m}} D$  Total monotone semantic transformer
- The iterates of  $F$  from  $\perp$  are assumed to be well-defined:  $F^0 \triangleq \perp$ ,  $F^{\delta+1} = F(F^\delta)$  and  $F^\lambda \triangleq \bigcup_{\delta < \lambda} F^\delta$ ,  $\lambda$  limit ordinal;
- The semantics is  $S \triangleq \text{lfp}_\perp^\sqsubseteq F = F^\epsilon$  where  $\epsilon$  is the order of the iterates (i.e. the least ordinal such that  $F(F^\epsilon) = F^\epsilon$ ).

## Benefits of a Fixpoint Presentation of the Semantics

- Many other equivalent possible presentations <sup>16</sup>:
  - equational,
  - constraint,
  - closure condition,
  - rule-based,
  - game-theoretic;

<sup>16</sup> P. Cousot and R. Cousot. Compositional and inductive semantic definitions in fixpoint, equational, constraint, closure-condition, rule-based and game-theoretic form, invited paper. In P. Wolper, ed., *Proc. 7th Int. Conf. on Computer Aided Verification, CAV '95*, LNCS 939, pp. 293–308. Springer-Verlag, 3–5 July 1995.

- By approximation, fixpoints directly lead to iterative program analysis algorithms <sup>17, 18</sup>;
- Fixpoint presentation of the semantics is not always possible (without further refinement of the semantic domain).

<sup>17</sup> P. Cousot and R. Cousot. Abstract interpretation: a unified lattice model for static analysis of programs by construction or approximation of fixpoints. In *Conference Record of the Fourth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 238–252, Los Angeles, California, 1977. ACM Press, New York, New York, USA.

<sup>18</sup> P. Cousot and R. Cousot. Systematic design of program analysis frameworks. In *Conference Record of the Sixth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pages 269–282, San Antonio, Texas, 1979. ACM Press, New York, New York, USA.

- Fixpoints directly lead to proof methods, e.g.:

- Scott induction:

$$\begin{aligned} P(\perp) \wedge \forall X : P(X) \Rightarrow P(F(X)) \wedge P \text{ admissible} \\ \Rightarrow P(\text{lfp}_{\perp}^{\sqsubseteq} F) \end{aligned}$$

(with the hypotheses of Kleene's fixpoint theorem);

- Park induction:

$$\begin{aligned} \text{lfp}_{\perp}^{\sqsubseteq} F \sqsubseteq P \\ \iff \exists I : F(I) \sqsubseteq I \wedge I \sqsubseteq P \end{aligned}$$

(with the hypotheses of Tarski's fixpoint theorem).

## Abstraction of Fixpoint Semantics

- Concrete semantics fixpoint semantics:

<ul style="list-style-type: none"> <li>- <math>\langle D, \sqsubseteq \rangle</math></li> <li>- <math>S[\tau] \in D</math></li> </ul>	concrete semantic domain concrete semantics of $\tau$ $\triangleq \text{lfp}_{\perp}^{\sqsubseteq} F$ where $F \in D \xrightarrow{m} D$ is $\sqsubseteq$ -monotonic
---	---

- Abstraction function:  $\alpha \in D \longrightarrow D^\sharp$

- Abstract semantics fixpoint semantics:

<ul style="list-style-type: none"> <li>- <math>D^\sharp</math></li> <li>- <math>S^\sharp[\tau] \triangleq \alpha(S[\tau]) \in D^\sharp</math></li> </ul>	abstract semantic domain abstract semantics of $\tau$
--	--

- Fixpoint characterization problem:

- Find  $\sqsubseteq^\sharp$  and  $F^\sharp \in D^\sharp \xrightarrow{m} D^\sharp$ ,  $\sqsubseteq^\sharp$ -monotonic such that:

$$\alpha(\text{lfp}_{\perp}^{\sqsubseteq} F) = \text{lfp}_{\perp}^{\sqsubseteq^\sharp} F^\sharp$$

## Kleene Fixpoint Transfer Theorem

If  $\langle \mathcal{D}^\sharp, F^\sharp \rangle$  and  $\langle \mathcal{D}^\sharp, F^\sharp \rangle$  are semantic specifications and

$$\alpha(\perp^\sharp) = \perp^\sharp$$

$$F^\sharp \circ \alpha = \alpha \circ F^\sharp$$

$$\forall \sqsubseteq^\sharp\text{-increasing chains } X_\kappa^\sharp, \kappa \in \Delta : \alpha(\bigsqcup_{\kappa \in \Delta}^\sharp X_\kappa^\sharp) = \bigsqcup_{\kappa \in \Delta}^\sharp \alpha(X_\kappa^\sharp)$$

then

$$\alpha(\text{lfp } \sqsubseteq^\sharp F^\sharp) = \text{lfp } \sqsubseteq^\sharp F^\sharp$$

**Note:** The condition  $F^\sharp \circ \alpha = \alpha \circ F^\sharp$  provides guidelines for designing  $F^\sharp$  when knowing  $F^\sharp$  and  $\alpha$ .

## Convergence


The convergence of the abstract iterates for  $F^\sharp$  (at  $\epsilon'$ ) is at least as fast as the convergence of the concrete iterates for  $F$  (at  $\epsilon$ , i.e.  $\epsilon' \leq \epsilon$ ).

*Proof*

$$\begin{aligned} & F(X^{\sharp\epsilon}) = X^{\sharp\epsilon} && \text{hypothesis} \\ \Rightarrow & \alpha(F(X^{\sharp\epsilon})) = \alpha(X^{\sharp\epsilon}) \\ \Rightarrow & F^\sharp(\alpha(X^{\sharp\epsilon})) = \alpha(X^{\sharp\epsilon}) && \text{since } F^\sharp \circ \alpha = \alpha \circ F^\sharp \\ \Rightarrow & F^\sharp(X^{\sharp\epsilon}) = X^{\sharp\epsilon} && \text{since } X^{\sharp\epsilon} = \alpha(X^{\sharp\epsilon}) \\ \Rightarrow & \epsilon' \leq \epsilon \end{aligned}$$

□

## Sketch of Proof of Kleene Fixpoint Transfer Theorem



## Abstraction function

- An important particular case of abstraction function:

$$\alpha \in \langle \mathcal{D}^\sharp, \sqsubseteq^\sharp \rangle \longmapsto \langle \mathcal{D}^\sharp, \sqsubseteq^\sharp \rangle$$

is when  $\alpha$  preserves existing lubs:

$$\alpha\left(\bigsqcup_{i \in \Delta}^\sharp x_i\right) = \bigsqcup_{i \in \Delta}^\sharp \alpha(x_i)$$

- In this case there exists a unique  $\gamma \in \langle \mathcal{D}^\sharp, \sqsubseteq^\sharp \rangle \longmapsto \langle \mathcal{D}^\sharp, \sqsubseteq^\sharp \rangle$  such that the pair  $\langle \alpha, \gamma \rangle$  is a Galois connection.

## Galois Connection

Given posets  $\langle \mathcal{D}^\natural, \sqsubseteq^\natural \rangle$  and  $\langle \mathcal{D}^\sharp, \sqsubseteq^\sharp \rangle$ , a *Galois connection* is a pair of maps such that:

$$\begin{aligned}\alpha &\in \mathcal{D}^\natural \longmapsto \mathcal{D}^\sharp \\ \gamma &\in \mathcal{D}^\sharp \longmapsto \mathcal{D}^\natural \\ \forall x \in \mathcal{D}^\natural : \forall y \in \mathcal{D}^\sharp : \alpha(x) \sqsubseteq^\sharp y &\Leftrightarrow x \sqsubseteq^\natural \gamma(y)\end{aligned}$$

in which case we write:

$$\langle \mathcal{D}^\natural, \sqsubseteq^\natural \rangle \xrightleftharpoons[\alpha]{\gamma} \langle \mathcal{D}^\sharp, \sqsubseteq^\sharp \rangle$$

If  $\alpha$  is surjective then we have a *Galois insertion* and write:

$$\langle \mathcal{D}^\natural, \sqsubseteq^\natural \rangle \xrightleftharpoons[\alpha]{\gamma} \langle \mathcal{D}^\sharp, \sqsubseteq^\sharp \rangle$$

## Example of Galois Connection: Elementwise Abstraction

• If

- $\emptyset \in \mathcal{D}^\natural \longmapsto \mathcal{D}^\sharp$
- $\alpha \in \wp(\mathcal{D}^\natural) \longmapsto \wp(\mathcal{D}^\sharp)$   
 $\alpha(X) \triangleq \{\emptyset(x) \mid x \in X\}$
- $\gamma \in \wp(\mathcal{D}^\sharp) \longmapsto \wp(\mathcal{D}^\natural)$   
 $\gamma(Y) \triangleq \{x \mid \emptyset(x) \in Y\}$

then

$$\langle \wp(\mathcal{D}^\natural), \subseteq \rangle \xrightleftharpoons[\alpha]{\gamma} \langle \wp(\mathcal{D}^\sharp), \subseteq \rangle$$

If  $\emptyset$  is surjective then so is  $\alpha$ .

*Proof*  $\alpha(X) \subseteq Y \Leftrightarrow \{\emptyset(x) \mid x \in X\} \subseteq Y \Leftrightarrow \forall x \in X : \emptyset(x) \in Y \Leftrightarrow X \subseteq \{x \mid \emptyset(x) \in Y\} \Leftrightarrow X \subseteq \gamma(Y)$ .  $\square$

## Tarski Fixpoint Transfer Theorem

If  $\langle \mathcal{D}^\natural, \sqsubseteq^\natural, \perp^\natural, \sqcup^\natural \rangle$  and  $\langle \mathcal{D}^\sharp, \sqsubseteq^\sharp, \perp^\sharp, \sqcup^\sharp \rangle$  are complete lattices,  $F^\natural \in \mathcal{D}^\natural \xrightarrow{\text{m}} \mathcal{D}^\natural$ ,  $F^\sharp \in \mathcal{D}^\sharp \xrightarrow{\text{m}} \mathcal{D}^\sharp$  are monotonic and

-  $\alpha$  is a complete  $\sqcap$ -morphism (a)

-  $F^\sharp \circ \alpha \sqsubseteq^\sharp \alpha \circ F^\natural$  (b)

-  $\forall y \in \mathcal{D}^\sharp : F^\sharp(y) \sqsubseteq^\sharp y \Rightarrow \exists x \in \mathcal{D}^\natural : \alpha(x) = y \wedge F^\natural(x) \sqsubseteq^\natural x$  (c)

then

$$\alpha(\text{lfp } \sqsubseteq^\natural F^\natural) = \text{lfp } \sqsubseteq^\sharp F^\sharp$$

*Proof*

$$\begin{aligned}(d) \quad F^\natural(x) \sqsubseteq^\natural x \\ \Rightarrow \alpha \circ F^\natural(x) \sqsubseteq^\natural \alpha(x) &\quad \text{since } \alpha \text{ is monotonic by (a)} \\ \Rightarrow F^\sharp \circ \alpha(x) \sqsubseteq^\sharp \alpha(x) &\quad \text{by (b)}\end{aligned}$$

$$(e) \quad \{\alpha(x) \mid F^\natural(x) \sqsubseteq^\natural x\} = \{y \mid F^\sharp(y) \sqsubseteq^\sharp y\} \quad \text{by (c) and (d)}$$

$$\begin{aligned}(f) \quad \sqcap^\sharp \{\alpha(x) \mid F^\natural(x) \sqsubseteq^\natural x\} &= \sqcap^\sharp \{y \mid F^\sharp(y) \sqsubseteq^\sharp y\} \quad \text{by (e)} \\ \Rightarrow \alpha(\sqcap^\natural \{x \mid F^\natural(x) \sqsubseteq^\natural x\}) &= \sqcap^\sharp \{y \mid F^\sharp(y) \sqsubseteq^\sharp y\} \quad \text{by (a)} \\ \Rightarrow \alpha(\text{lfp } \sqsubseteq^\natural F^\natural) &= \text{lfp } \sqsubseteq^\sharp F^\sharp \quad \text{by Tarski's fixpt th.}\end{aligned}$$

$\square$

## TRACE SEMANTICS

© P. Cousot

33

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Transition System

- A transition system is a pair  $\langle \Sigma, \tau \rangle$  where:
  - $\Sigma$  is a (non-empty) set of states,
  - We could also consider actions as in process algebra,
  - $\tau \subseteq \Sigma \times \Sigma$  is the binary transition relation between a state and its possible successors;
- We write  $s \tau s'$  or  $\tau(s, s')$  for  $\langle s, s' \rangle \in \tau$  using the isomorphism  $\wp(\Sigma \times \Sigma) \simeq (\Sigma \times \Sigma) \longmapsto \mathbb{B}$ ;
- $\mathbb{B} \stackrel{\Delta}{=} \{\text{tt}, \text{ff}\}$  is the set of boolean values;
- $\check{\tau} \stackrel{\Delta}{=} \{s \in \Sigma \mid \forall s' \in \Sigma : \neg(s \tau s')\}$  is the set of final/blocking states.

© P. Cousot

34

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Sequences Finite Sequences

- $\mathcal{A}$  non-empty alphabet
- $\mathcal{A}^{\vec{0}} \stackrel{\Delta}{=} \{\vec{\varepsilon}\}$  empty sequence
- $\mathcal{A}^{\vec{n}} \stackrel{\Delta}{=} [0, n - 1] \longmapsto \mathcal{A}$  when  $n > 0$  finite sequences of length  $n$
- $\mathbb{N}_+ \stackrel{\Delta}{=} \{n \in \mathbb{N} \mid n > 0\}$  positive naturals
- $\mathcal{A}^{\vec{+}} \stackrel{\Delta}{=} \bigcup_{n \in \mathbb{N}_+} \mathcal{A}^{\vec{n}}$  non-empty finite sequences
- $\mathcal{A}^{\vec{*}} \stackrel{\Delta}{=} \mathcal{A}^{\vec{+}} \cup \{\vec{\varepsilon}\}$  finite sequences
- The length of a finite sequence  $\sigma \in \mathcal{A}^{\vec{n}}$  is  $|\sigma| \stackrel{\Delta}{=} n$ ;

© P. Cousot

35

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Infinite Sequences

- $\mathcal{A}^{\vec{\omega}} \stackrel{\Delta}{=} \mathbb{N} \longmapsto \mathcal{A}$  infinite sequences
- $\mathcal{A}^{\infty} \stackrel{\Delta}{=} \mathcal{A}^{\vec{*}} \cup \mathcal{A}^{\vec{\omega}}$  sequences
- $\mathcal{A}^{\vec{\infty}} \stackrel{\Delta}{=} \mathcal{A}^{\vec{+}} \cup \mathcal{A}^{\vec{\omega}}$  non-empty sequences
- The length of an infinite sequence  $\sigma \in \mathcal{A}^{\vec{\omega}}$  is  $|\sigma| \stackrel{\Delta}{=} \omega$

© P. Cousot

36

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Junction of Finite Sequences

- Joinable non-empty finite sequences:

$$\alpha_0 \dots \alpha_{\ell-1} ? \beta_0 \dots \beta_{m-1} \text{ iff } \alpha_{\ell-1} = \beta_0$$

- Their join is:

$$\frac{\begin{array}{c} \alpha_0 \dots \alpha_{\ell-1} \\ = \\ \beta_0 \beta_1 \dots \beta_{m-1} \end{array}}{\alpha_0 \dots \alpha_{\ell-1} \cap \beta_0 \dots \beta_{m-1} \stackrel{\Delta}{=} \alpha_0 \dots \alpha_{\ell-1} \beta_1 \dots \beta_{m-1}}$$

$$\begin{aligned} \alpha_0 \dots \alpha_{\ell-1} ? \beta_0 \dots \beta_{m-1} &\text{ is true} \\ \alpha_0 \dots \alpha_{\ell-1} ? \beta_0 \dots \beta_m &\dots \text{ is true} \\ \alpha_0 \dots \alpha_{\ell-1} ? \beta_0 \dots \beta_m &\dots \text{ iff } \alpha_{\ell-1} = \beta_0 \end{aligned}$$

- Their join is:

$$\frac{\begin{array}{c} \alpha_0 \dots \alpha_{\ell-1} \cap \beta_0 \dots \beta_{m-1} \stackrel{\Delta}{=} \alpha_0 \dots \alpha_{\ell-1} \\ \alpha_0 \dots \alpha_{\ell-1} \cap \beta_0 \dots \beta_m \stackrel{\Delta}{=} \alpha_0 \dots \alpha_{\ell-1} \\ \alpha_0 \dots \alpha_{\ell-1} \\ = \\ \beta_0 \beta_1 \dots \beta_m \dots \end{array}}{\alpha_0 \dots \alpha_{\ell-1} \cap \beta_0 \dots \beta_m \stackrel{\Delta}{=} \alpha_0 \dots \alpha_{\ell-1} \beta_1 \dots \beta_m \dots}$$

## Junction of Infinitary Sequences

- Joinable infinitary sequences:


## Junction of Sets of Sequences

- For sets  $A$  and  $B \in \wp(\mathcal{A}^{\vec{\alpha}})$  of non-empty sequences, we have:
  - $- A \cap B \stackrel{\Delta}{=} \{\alpha \cap \beta \mid \alpha \in A \wedge \beta \in B \wedge \alpha ? \beta\}$  junction
- $A \cap (\bigcup_{i \in \Delta} B_i) = \bigcup_{i \in \Delta} (A \cap B_i)$  and  $(\bigcup_{i \in \Delta} A_i) \cap B = \bigcup_{i \in \Delta} (A_i \cap B)$
- Not co-continuous on  $\wp(\mathcal{A}^{\vec{\alpha}})$  ! Counter example ( $\mathcal{A} = \{a\}$ ):
  - $- A = \{a^\omega\},$
  - $- B_n = \{a^\ell \mid \ell \in \mathbb{N} \wedge \ell > n\}, n \in \mathbb{N}$  is a  $\subseteq$ -decreasing chain,
  - $- A \cap (\bigcap_{n \in \mathbb{N}} B_n) = \emptyset$  and  $(\bigcap_{n \in \mathbb{N}} A \cap B_n) = \{a^\omega\}.$

## Trace Semantics

- $\langle \Sigma, \tau \rangle$  transition system
- $\tau^{\vec{n}} \stackrel{\Delta}{=} \{ \sigma \in \Sigma^{\vec{n}} \mid \forall i < n - 1 : \sigma_i \tau \sigma_{i+1} \}$  partial traces of length  $n$
- $\check{\tau} \stackrel{\Delta}{=} \{ s \in \Sigma \mid \forall s' \in \Sigma : \neg(s \tau s') \}$  final/blocking states
- $\tau^{\vec{n}} \stackrel{\Delta}{=} \{ \sigma \in \tau^{\vec{n}} \mid \sigma_{n-1} \in \check{\tau} \}$  complete traces of length  $n$
- $\tau^{\vec{+}} \stackrel{\Delta}{=} \bigcup_{n \in \mathbb{N}_+} \tau^{\vec{n}}$  finite complete traces
- $\tau^{\vec{\omega}} \stackrel{\Delta}{=} \{ \sigma \in \Sigma^{\vec{\omega}} \mid \forall i \in \mathbb{N} : \sigma_i \tau \sigma_{i+1} \}$  infinite traces
- $\tau^{\vec{\infty}} \stackrel{\Delta}{=} \tau^{\vec{+}} \cup \tau^{\vec{\omega}}$  complete traces

$$\text{Sketch of Proof of } \text{lfp}_{\emptyset}^{\subseteq} F^{\vec{+}} = \bigcup_{i \in \mathbb{N}_+} \tau^{\vec{i}} = \tau^{\vec{+}}$$



## Fixpoint Characterization of $\tau^{\vec{+}}$ (finite complete execution traces)

$$\tau^{\vec{+}} = \text{lfp}_{\emptyset}^{\subseteq} F^{\vec{+}}$$

where the set of finite traces transformer  $F^{\vec{+}}$  is:

$$F^{\vec{+}}(X) \stackrel{\Delta}{=} \tau^{\vec{1}} \cup \tau^{\vec{2}} \cap X$$

Note:  $F^{\vec{+}}$  is a complete  $\cup$ -morphism:  $\bigcup_i F^{\vec{+}}(X_i) = F^{\vec{+}}(\bigcup_i X_i)$ .

## Fixpoint Characterization of $\tau^{\vec{\omega}}$ (infinite execution traces)


$$\tau^{\vec{\omega}} = \text{gfp}_{\Sigma^{\vec{\omega}}}^{\subseteq} F^{\vec{\omega}}$$

where the set of infinite traces transformer  $F^{\vec{\omega}}$  is:

$$F^{\vec{\omega}}(X) \stackrel{\Delta}{=} \tau^{\vec{2}} \cap X$$

Note:  $F^{\vec{\omega}}$  is a complete  $\cap$ -morphism:  $\bigcap_i F^{\vec{\omega}}(X_i) = F^{\vec{\omega}}(\bigcap_i X_i)$ .

**Sketch of Proof of**  $\text{gfp}_{\Sigma^{\vec{\omega}}}^{\subseteq} F^{\vec{\omega}} = \bigcap_{n \in \mathbb{N}} \tau^{\vec{n}} \cap \Sigma^{\vec{\omega}} = \tau^{\vec{\omega}}$



then:

- $\langle \wp(\Sigma^{\vec{\omega}}), \subseteq^{\vec{\omega}}, \perp^{\vec{\omega}}, \sqcup^{\vec{\omega}} \rangle$  is a complete lattice (resp. cpo)
- $F^{\vec{\omega}}$  is monotonic (resp. continuous, a complete join morphism)
- $\text{lfp}_{\perp^{\vec{\omega}}}^{\subseteq^{\vec{\omega}}} F^{\vec{\omega}} = \text{lfp}_{\perp^{\vec{\omega}}}^{\sqsubseteq^{\vec{\omega}}} F^{\vec{\omega}} \cup \text{lfp}_{\perp^{\vec{\omega}}}^{\sqsubseteq^{\vec{\omega}}} F^{\vec{\omega}}$

### (Trivial) bi-fixpoint theorem

If

- $\Sigma^{\vec{\tau}}, \Sigma^{\vec{\omega}}$  is a partition of  $\Sigma^{\vec{\infty}}$
- $\langle \wp(\Sigma^{\vec{\tau}}), \sqsubseteq^{\vec{\tau}}, \perp^{\vec{\tau}}, \sqcup^{\vec{\tau}} \rangle$  (resp.  $\langle \wp(\Sigma^{\vec{\omega}}), \sqsubseteq^{\vec{\omega}}, \perp^{\vec{\omega}}, \sqcup^{\vec{\omega}} \rangle$ ) is a complete lattice (resp. cpo)
- $F^{\vec{\tau}} \in \wp(\Sigma^{\vec{\tau}}) \xrightarrow{m} \wp(\Sigma^{\vec{\tau}})$  (resp.  $F^{\vec{\omega}} \in \wp(\Sigma^{\vec{\omega}}) \xrightarrow{m} \wp(\Sigma^{\vec{\omega}})$ ) is monotonic (resp. continuous, a complete join morphism)
- $X^{\vec{\tau}} \triangleq X \cap \Sigma^{\vec{\tau}}, X^{\vec{\omega}} \triangleq X \cap \Sigma^{\vec{\omega}}$
- $F^{\vec{\infty}}(X) \triangleq F^{\vec{\tau}}(X^{\vec{\tau}}) \cup F^{\vec{\omega}}(X^{\vec{\omega}})$
- $X \sqsubseteq^{\vec{\infty}} Y \triangleq X^{\vec{\tau}} \sqsubseteq^{\vec{\tau}} Y^{\vec{\tau}} \wedge X^{\vec{\omega}} \sqsubseteq^{\vec{\omega}} Y^{\vec{\omega}}$
- $\perp^{\vec{\infty}} \triangleq \perp^{\vec{\tau}} \cup \perp^{\vec{\omega}}$
- $\sqcup^{\vec{\infty}}_i X_i \triangleq \bigsqcup_i^{\vec{\tau}} X_i^{\vec{\tau}} \cup \bigsqcup_i^{\vec{\omega}} X_i^{\vec{\omega}}$

### Approximation and Computational Orderings

- $\langle \wp(\Sigma^{\vec{\infty}}), \subseteq^{\vec{\infty}}, \perp^{\vec{\infty}}, \sqcup^{\vec{\infty}} \rangle$  is a complete lattice (or cpo) for the *computational ordering*  $\subseteq^{\vec{\infty}}$ ;
- $\langle \wp(\Sigma^{\vec{\infty}}), \subseteq, \emptyset, \cup \rangle$  is a complete lattice for the *approximation ordering*  $\subseteq$  (logical implication);
- Sometimes further abstractions identify  $\subseteq^{\vec{\infty}}$  and  $\subseteq$  (e.g. strictness analysis).

## Fixpoint Characterization of $\tau^\infty$ (complete execution traces)

$$\tau^\infty = \tau^{\vec{+}} \cup \tau^{\vec{\omega}} = \text{lfp}_{\emptyset}^{\subseteq} F^{\vec{+}} \cup \text{lfp}_{\Sigma^{\vec{\omega}}}^{\supseteq} F^{\vec{\omega}} = \text{lfp}_{\Sigma^\infty}^{\sqsubseteq^\infty} F^\infty$$

by the bifixpoint theorem where the set of complete traces transformer  $F^\infty$  is:

$$F^\infty(X) \triangleq \tau^{\vec{1}} \cup \tau^{\vec{2}} \cap X$$

*Proof*

$$\begin{aligned} F^\infty(X) &\triangleq F^{\vec{+}}(X^{\vec{+}}) \cup F^{\vec{\omega}}(X^{\vec{\omega}}) \\ &= \tau^{\vec{1}} \cup \tau^{\vec{2}} \cap X^{\vec{+}} \cup \tau^{\vec{2}} \cap X^{\vec{\omega}} \\ &= \tau^{\vec{1}} \cup \tau^{\vec{2}} \cap (X^{\vec{+}} \cup X^{\vec{\omega}}) \\ &= \tau^{\vec{1}} \cup \tau^{\vec{2}} \cap X \end{aligned}$$

□

## Scott's thesis (slightly revisited)

The semantics of a program can be expressed as the least fixpoint of a continuous operator (even in presence of unbounded nondeterminism), *for a sufficiently refined semantic domain.*

## Continuity of the trace transformer $F^\infty(X)$

Unbounded non-determinism does not imply absence of continuity of the transformer of the fixpoint semantics:

*Proof*

$$\begin{aligned} \bigsqcup_i^\infty F^\infty(X_i) &= \bigsqcup_i^\infty \tau^{\vec{1}} \cup \tau^{\vec{2}} \cap X_i \\ &= \bigcup_i (\tau^{\vec{1}} \cup \tau^{\vec{2}} \cap X_i^{\vec{+}}) \cup \bigcap_i (\tau^{\vec{2}} \cap X_i^{\vec{\omega}}) \\ &= \tau^{\vec{1}} \cup \tau^{\vec{2}} \cap \left( \bigcup_i X_i^{\vec{+}} \cup \bigcap_i X_i^{\vec{\omega}} \right) \\ &= F^\infty(\bigsqcup_i^\infty X_i) \end{aligned}$$

□

## TRANSITION VERSUS TRACE SEMANTICS

## Maximal Trace Semantics/Transition Semantics

The transition/small-step operational semantics is an abstraction of the maximal trace semantics:

$$\tau = \alpha^\tau(\vec{\tau}^\infty)$$

where

- the abstraction collects possible transitions  $\alpha^\tau(T) \triangleq \{\langle s, s' \rangle \mid \exists \sigma \in \Sigma^\vec{x} : \exists \sigma' \in \Sigma^\vec{x} : \sigma \cdot ss' \cdot \sigma' \in T\}$ ;
- the concretization builds maximal execution traces  $\gamma^\tau(t) \triangleq t^\infty$ ;
- $\langle \wp(\Sigma^\infty), \subseteq \rangle \xleftarrow[\alpha^\tau]{\gamma^\tau} \langle \wp(\Sigma \times \Sigma), \subseteq \rangle$ .

## RELATIONAL SEMANTICS

## The Transition Abstraction is Approximate

In general:

$$T \subsetneq \gamma^\tau(\alpha^\tau(T))$$

Counter-example:

- set of fair traces  $T = \{a^n b \mid n \in \mathbb{N}\}$
- $\alpha^\tau(T) = \{\langle a, a \rangle, \langle a, b \rangle\}$
- $\gamma^\tau(\alpha^\tau(T)) = \{a^n b \mid n \in \mathbb{N}\} \cup \{a^\omega\}$  is unfair for  $b$ .

## Finite Relational Abstraction

Replace finite execution traces  $\sigma_0 \sigma_1 \dots \sigma_{n-1}$  by their initial/final states  $\langle \sigma_0, \sigma_{n-1} \rangle$ :

- $\text{@}^+ \in \Sigma^\vec{x} \longmapsto (\Sigma \times \Sigma)$   
 $\text{@}^+(\sigma) \triangleq \langle \sigma_0, \sigma_{n-1} \rangle, \quad n \in \mathbb{N}_+, \sigma \in \Sigma^\vec{n}$
- $\alpha^+(X) \triangleq \{\text{@}^+(\sigma) \mid \sigma \in X\}$   
 $\gamma^+(Y) \triangleq \{\sigma \mid \text{@}^+(\sigma) \in Y\}$
- $\langle \wp(\Sigma^\vec{x}), \subseteq \rangle \xleftarrow[\alpha^+]{\gamma^+} \langle \wp(\Sigma \times \Sigma), \subseteq \rangle$

## Finitary Relational Semantics of a Transition System $\langle \Sigma, \tau \rangle$

- Finitary relational / big-step operational / natural semantics:

$$\tau^+ \triangleq \alpha^+(\tau^\vec{\tau}) = \alpha^+(\text{lfp}_\emptyset^\subseteq F^\vec{\tau})$$

- Fixpoint characterization:

$$\begin{aligned} \tau^+ &= \text{lfp}_\emptyset^\subseteq F^+ \\ F^+(X) &\triangleq \check{\tau} \cup \tau \circ X \\ \check{\tau} &\triangleq \{\langle s, s \rangle \in \Sigma \mid \forall s' \in \Sigma : \neg(s \tau s')\} \end{aligned}$$

*Proof*

- $\alpha^+(\emptyset) \triangleq \{\alpha^+(\sigma) \mid \sigma \in \emptyset\} = \emptyset$
- $\alpha^+ \circ F^\vec{\tau} = \lambda X \cdot \alpha^+(\tau^{\vec{1}} \cup \tau^{\vec{2}} \cap X)$   
 $= \lambda X \cdot \alpha^+(\tau^{\vec{1}}) \cup \alpha^+(\tau^{\vec{2}} \cap X)$   
 $= \lambda X \cdot \{\langle s, s \rangle \in \Sigma \mid \forall s' \in \Sigma : \neg(s \tau s')\} \cup \alpha^+(\tau^{\vec{2}} \cap X)$   
 $= \lambda X \cdot \check{\tau} \cup \{\alpha^+(\eta \cap \xi) \mid \eta \in \tau^{\vec{2}} \wedge \xi \in X \wedge \eta \not\sqsupseteq \xi\}$   
 $= \lambda X \cdot \check{\tau} \cup \{\langle \eta_0, \xi_{n-1} \rangle \mid \eta_0 \tau \xi_0 \wedge n \in \mathbb{N}_+ \wedge \xi \in X \cap \Sigma^{\vec{n}}\}$   
 $= \lambda X \cdot \check{\tau} \cup \{\langle s, s' \rangle \mid \exists s'' : s \tau s'' \wedge \langle s'', s' \rangle \in \alpha^+(X)\}$   
 $= \lambda X \cdot \check{\tau} \cup \tau \circ \alpha^+(X)$   
 $= F^+ \circ \alpha^+$
- $\alpha^+$  is continuous (Galois connection)
- $\tau^+ = \alpha^+(\text{lfp}_\emptyset^\subseteq F^\vec{\tau}) = \text{lfp}_\emptyset^\subseteq F^+$  by Kleene's fixpoint transfer th.

□

- $\alpha^+$  is a  $\sqcap$ -morphism but not co-continuous hence not a complete  $\sqcap$ -morphism.

*Proof*

- $X^k \triangleq \{a^n b \mid n \geq k\}$
- $X^k, k \in \mathbb{N}_+$  is  $\sqsubseteq$ -decreasing
- $\bigcap_{k \in \mathbb{N}_+} \alpha^+(X^k) = \bigcap_{k \in \mathbb{N}_+} \{\langle a, b \rangle\} = \{\langle a, b \rangle\}$
- $\bigcap_{k \in \mathbb{N}_+} X^k = \emptyset$  since  $a^n b \in \bigcap_{k \in \mathbb{N}_+} X^k$  for  $n \in \mathbb{N}_+$  is in contradiction with  $a^n b \notin X^{n+1}$
- $\alpha^+(\bigcap_{k \in \mathbb{N}_+} X^k) = \alpha^+(\emptyset) = \emptyset$

□

- It follows that Tarski fixpoint transfer would not have been applicable.

## Infinitary Relational Abstraction

Replace infinite execution traces  $\sigma_0 \sigma_1 \dots \sigma_n \dots$  by their initial state  $\langle \sigma_0, \perp \rangle$ , making non-termination by Scott's  $\perp$ :

- $\text{@}^\omega \in \Sigma^{\vec{\omega}} \longmapsto \Sigma \times \{\perp\}$ <sup>19</sup>  
 $\perp \notin \Sigma$   
 $\text{@}^\omega(\sigma) \triangleq \langle \sigma_0, \perp \rangle, \sigma \in \Sigma^{\vec{\omega}}$
- $\alpha^\omega(X) \triangleq \{\text{@}^\omega(\sigma) \mid \sigma \in X\}$   
 $\gamma^\omega(Y) \triangleq \{\sigma \mid \text{@}^\omega(\sigma) \in Y\}$
- $\langle \wp(\Sigma^{\vec{\omega}}), \subseteq \rangle \xleftarrow[\alpha^\omega]{\gamma^\omega} \langle \wp(\Sigma \times \{\perp\}), \subseteq \rangle$

<sup>19</sup> or isomorphically  $\alpha^\omega \in \wp(\Sigma^{\vec{\omega}}) \longmapsto \wp(\Sigma)$ .

- $\alpha^\omega$  is a complete  $\cup$ -morphism (Galois connection, hence continuous) and a  $\cap$ -morphism but not co-continuous.

*Proof*

- $X^k \triangleq \{a^n b^\omega \mid n \geq k\}$
- $X^k, k \in \mathbb{N}_+$  is  $\subseteq$ -decreasing
- $\bigcap_{k \in \mathbb{N}_+} \alpha^\omega(X^k) = \bigcap_{k \in \mathbb{N}_+} \{\langle a, \perp \rangle\} = \{\langle a, \perp \rangle\}$
- $\bigcap_{k \in \mathbb{N}_+} X^k = \emptyset$  since  $a^n b^\omega \in \bigcap_{k \in \mathbb{N}_+} X^k$  for  $n \in \mathbb{N}_+$  is in contradiction with  $a^n b^\omega \notin X^{n+1}$
- $\alpha^\omega(\bigcap_{k \in \mathbb{N}_+} X^k) = \alpha^\omega(\emptyset) = \emptyset$

□

- It follows that Kleene dual fixpoint transfer does not apply.

*Proof*

- $\alpha^\omega$  is a complete  $\cup$ -morphism (G.c.) hence a complete meet morphism for  $\supseteq$ .

$$\begin{aligned} \bullet \alpha^\omega \circ F^{\vec{\omega}} &= \lambda X \cdot \alpha^\omega(\tau^{\vec{\omega}} \cap X) \\ &= \lambda X \cdot \{\alpha^\omega(\eta \cap \xi) \mid \eta \in \tau^{\vec{\omega}} \wedge \xi \in X \wedge \eta \supseteq \xi\} \\ &= \lambda X \cdot \{\langle \eta_0, \perp \rangle \mid \eta_0 \tau \xi_0 \wedge \xi \in X\} \\ &= \lambda X \cdot \{\langle s, \perp \rangle \mid \exists s' : s \tau s' \wedge \langle s', \perp \rangle \in \alpha^\omega(X)\} \\ &= \lambda X \cdot \tau \circ \alpha^\omega(X) \\ &= F^\omega \circ \alpha^\omega \end{aligned}$$

- We prove that  $\forall Y \in \wp(\Sigma \times \{\perp\}) : F^\omega(Y) \supseteq Y \Rightarrow \exists X \in \Sigma^{\vec{\omega}} : \alpha^\omega(X) = Y \wedge F^{\vec{\omega}}(X) \supseteq X$ :

- $X \triangleq \{\sigma \in \tau^{\vec{\omega}} \mid \forall i \in \mathbb{N} : \langle \sigma_i, \perp \rangle \in Y\}$

- We first prove that  $\alpha^\omega(X) = Y$ :

- \*  $\alpha^\omega(X) \subseteq Y$  is obvious since  $\sigma \in X$  implies  $\langle \sigma_0, \perp \rangle \in Y$ .

## Infinitary Relational Semantics of a Transition System $\langle \Sigma, \tau \rangle$

- Infinitary relational semantics:

$$\tau^\omega \triangleq \alpha^\omega(\tau^{\vec{\omega}}) = \alpha^\omega(\text{gfp}_{\Sigma^{\vec{\omega}}}^{\subseteq} F^{\vec{\omega}}) = \alpha^\omega(\text{lfp}_{\Sigma^{\vec{\omega}}}^{\supseteq} F^{\vec{\omega}})$$

- Fixpoint characterization:

$$\begin{aligned} \tau^\omega &= \text{lfp}_{\Sigma \times \{\perp\}}^{\supseteq} F^\omega = \text{gfp}_{\Sigma \times \{\perp\}}^{\subseteq} F^\omega \\ F^\omega(X) &= \tau \circ X \end{aligned}$$

- \*  $Y \subseteq \alpha^\omega(X)$

- (a)  $Y \subseteq F^\omega(Y) = \tau \circ Y = \{\langle s, \perp \rangle \mid \exists s' : s \tau s' \wedge \langle s', \perp \rangle \in Y\}$

- (b) If  $\sigma_0 \dots \sigma_n$  is such that  $\sigma_i \tau \sigma_{i+1}$ ,  $i < n$  and  $\langle \sigma_i, \perp \rangle \in Y$ ,  
 $i \leq n$  then  $\langle \sigma_n, \perp \rangle \in Y$  and (a) imply  $\exists \sigma_{n+1} : \sigma_n \tau \sigma_{n+1} \wedge \langle \sigma_{n+1}, \perp \rangle \in Y$ . So, by induction, we can built  $\sigma \in \tau^{\vec{\omega}}$  such that  $\forall i \in \mathbb{N} : \langle \sigma_i, \perp \rangle \in Y$ . We have  $\sigma \in X$  and  $\langle \sigma_0, \perp \rangle \in \alpha^\omega(X)$  proving that  $Y \subseteq \alpha^\omega(X)$ ;

- Next, we prove  $F^{\vec{\omega}}(X) \supseteq X$ :  $F^{\vec{\omega}}(X) \supseteq X \iff X \subseteq \tau^{\vec{\omega}} \cap X \iff \forall \sigma \in X : \sigma_0 \tau \sigma_1 \wedge \sigma \geq^1 \in X$  where the suffix  $\sigma \geq^1$  is  $\eta$  such that  $\forall i \in \mathbb{N} : \eta_i = \sigma_{i+1}$ .

- \*  $\sigma_0 \tau \sigma_1$  holds since  $X \subseteq \tau^{\vec{\omega}}$ ,

- \*  $\eta \in \tau^{\vec{\omega}}$  and  $\forall i \in \mathbb{N} : \langle \eta_i, \perp \rangle = \langle \sigma_i, \perp \rangle \in Y$  proving that  $\eta = \sigma \geq^1 \in X$ .

- We conclude by Tarski's fixpoint transfer theorem.

□


## Transfinite Iterations

- Transition system  $\langle \Sigma, \tau \rangle$ :

$$\Sigma \stackrel{\Delta}{=} \{s\} \cup \{s_{ij} \mid 0 \leq j \leq i\}$$

elements of  $\Sigma$  are distinct  
two by two

$$\begin{aligned}\tau &\stackrel{\Delta}{=} \{\langle s, s_{ii} \rangle \mid i \geq 0\} \cup \\ &\quad \{\langle s_{ij}, s_{ij-1} \rangle \mid 0 < j \leq i\} \\ \tau^{\vec{\omega}} &= \emptyset \\ \tau^{\omega} &= \emptyset\end{aligned}$$



- Iterates:

$$\begin{aligned}- X^0 &= \{\langle s, \perp \rangle\} \cup \{\langle s_{ij}, \perp \rangle \mid 0 \leq j \leq i\} \\ - X^1 &= F^\omega(X^0) = \{\langle s, \perp \rangle\} \cup \{\langle s_{ij}, \perp \rangle \mid 1 \leq j \leq i\} \\ \dots \\ - X^n &= \{\langle s, \perp \rangle\} \cup \{\langle s_{ij}, \perp \rangle \mid n \leq j \leq i\} \\ \dots \\ - X^\omega &= \bigcap_{n \in \mathbb{N}} X^n = \{\langle s, \perp \rangle\} \\ - X^{\omega+1} &= F^\omega(X^\omega) = \emptyset = \text{gfp}_{\Sigma \times \{\perp\}}^{\subseteq} F^\omega = \tau^\omega\end{aligned}$$

$$F^\omega(X) = \tau \circ X$$

## Bifinite Relational Abstraction

- $\alpha^\infty \in \wp(\Sigma^{\vec{\omega}}) \longmapsto \wp(\Sigma \times \Sigma_\perp)$ ,  $\Sigma_\perp \stackrel{\Delta}{=} \Sigma \cup \{\perp\}$

$$\alpha^\infty(X) \stackrel{\Delta}{=} \alpha^+(X^{\vec{\tau}}) \cup \alpha^\omega(X^{\vec{\omega}}) \text{ where } X^+ = X \cap (\Sigma \times \Sigma) \text{ and } X^\omega = X \cap (\Sigma \times \{\perp\})$$

- Bifinite relational semantics:

$$\begin{aligned}\tau^\infty &\stackrel{\Delta}{=} \alpha^\infty(\tau^{\vec{\omega}}) \\ &= \alpha^+(\alpha^\infty)^{\vec{\tau}} \cup \alpha^\omega((\alpha^\infty)^{\vec{\omega}}) \\ &= \alpha^+(\tau^{\vec{\tau}}) \cup \alpha^\omega(\tau^{\vec{\omega}}) \\ &= \tau^+ \cup \tau^\omega\end{aligned}$$

## Fixpoint Bifinite Relational Semantics of a Transition System $\langle \Sigma, \tau \rangle$

- $\tau^\infty \stackrel{\Delta}{=} \tau^+ \cup \tau^\omega$ 

$$\begin{aligned}&= \text{lfp}_{\emptyset}^{\subseteq} \lambda X \cdot \check{\tau} \cup \tau \circ X \cup \text{lfp}_{\Sigma \times \{\perp\}}^{\supseteq} \lambda X \cdot \tau \circ X \\ &= \text{lfp}_{\perp \infty}^{\sqsubseteq \infty} F^\infty \quad \text{by the bi-fixpoint theorem, where:}\end{aligned}$$
- $F^\infty(X) \stackrel{\Delta}{=} \lambda X \cdot \check{\tau} \cup \tau \circ X^+ \cup \tau \circ X^\omega = \lambda X \cdot \check{\tau} \cup \tau \circ (X^+ \cup X^\omega)$ 

$$\begin{aligned}&= \lambda X \cdot \check{\tau} \cup \tau \circ X \\ \bullet \quad X \sqsubseteq \infty Y &\stackrel{\Delta}{=} X^+ \subseteq Y^+ \wedge X^\omega \supseteq Y^\omega \\ \bullet \quad \perp^\infty &\stackrel{\Delta}{=} \emptyset \cup (\Sigma \times \{\perp\}) = \Sigma \times \{\perp\} \\ \bullet \quad \bigsqcup_i^\infty X_i &\stackrel{\Delta}{=} \bigcup_i X_i^+ \cup \bigcap_i X_i^\omega \\ \bullet \quad \langle \wp(\Sigma \times \Sigma_\perp), \sqsubseteq^\infty, \perp^\infty, \bigsqcup^\infty \rangle &\text{ is a complete lattice.}\end{aligned}$$

## Abstraction by Parts

$$\tau^\infty = \alpha^\infty(\text{lfp}_{\perp^\infty}^{\sqsubseteq^\infty} F^\infty) = \text{lfp}_{\perp^\infty}^{\sqsubseteq^\infty} F^\infty$$

- The finitary part transfers through  $\alpha^+$  by Kleene's fixpoint transfer theorem (but Tarski's one is not applicable);
- The infinitary part transfers through  $\alpha^\omega$  by Tarski's fixpoint transfer theorem (but Kleene's one is not applicable);
- The whole transfers through  $\alpha^\infty$  by parts using the bifixpoint theorem (although Kleene's and Tarski's fixpoint transfer theorems are not applicable).

## Denotational/Functional Nondeterministic Abstraction

We use the complete order isomorphism:

$$\begin{array}{c} \langle \wp(\Sigma \times \Sigma_\perp), \sqsubseteq^\infty, \perp^\infty, \top^\infty, \sqcup^\infty, \sqcap^\infty \rangle \\ \xleftrightarrow[\alpha^\natural]{\gamma^\natural} \\ \langle \Sigma \longmapsto \wp(\Sigma_\perp), \dot{\sqsubseteq}^\natural, \dot{\perp}^\natural, \dot{\top}^\natural, \dot{\sqcup}^\natural, \dot{\sqcap}^\natural \rangle \end{array}$$

defined by the right-image of a relation:

$$\begin{aligned} \alpha^\natural(r) &= \lambda s \cdot \{s' \in \Sigma_\perp \mid r(s, s')\} \\ \gamma^\natural(f) &= \{\langle s, s' \rangle \mid s' \in f(s)\} \end{aligned}$$

## Natural Fixpoint Denotational/Functional Nondeterministic Semantics of a Transition System $\langle \Sigma, \tau \rangle$

- $\tau^\natural \triangleq \alpha^\natural(\tau^\infty)$   
 $= \text{lfp}_{\dot{\sqsubseteq}^\natural}^{\dot{\sqcup}^\natural} F^\natural$
- $F^\natural(f) \triangleq \lambda s \cdot (\forall s' \in \Sigma : \neg(s \tau s') ? \{s\} \mid \{s' \mid \exists s'' \in \Sigma : s \tau s'' \wedge s' \in f(s'')\})$

*Proof*

Trivial application of Kleene's fixpoint transfert theorem for the complete order-isomorphism  $\alpha^\natural$ .


□

## Computational Ordering


$$\begin{aligned} f \dot{\sqsubseteq}^\natural g &\triangleq \gamma^\natural(f) \sqsubseteq^\infty \gamma^\natural(g) \\ &= \{\langle s, s' \rangle \mid s' \in f(s) \cap \Sigma\} \subseteq \{\langle s, s' \rangle \mid s' \in g(s) \cap \Sigma\} \\ &\quad \wedge \{\langle s, s' \rangle \mid f(s) = \perp\} \subseteq \{\langle s, s' \rangle \mid g(s) = \perp\} \\ &= \forall s \in \Sigma : f(s)^+ \subseteq g(s)^+ \wedge f(s)^\omega \supseteq g(s)^\omega \\ &\quad \text{where } X^+ \triangleq X \cap \Sigma \text{ and } X^\omega \triangleq X \cap \{\perp\} \\ &= \forall s \in \Sigma : f(s) \sqsubseteq^\natural g(s) \\ &\quad \text{where } X \sqsubseteq^\natural Y \triangleq X^+ \subseteq Y^+ \wedge X^\omega \supseteq Y^\omega \end{aligned}$$

This is not the classical Egli-Milner ordering!

## Orderings for the Nondeterministic Denotational Semantics, $\Sigma = \{a, b\}$



Computational ordering  $\sqsubseteq^\sharp$



Egli-Milner ordering  $\sqsubseteq^{\text{EM}}$

$\overline{\quad}$  : possible iterates of  $F^\sharp$

## Plotkin's Fixpoint Denotational/Functional Nondeterministic Semantics of a Transition System $\langle \Sigma, \tau \rangle$

- $\tau^\sharp \stackrel{\Delta}{=} \alpha^\sharp(\tau^\infty)$   
 $= \text{lfp}_{\lambda s \bullet \{\perp\}}^{\sqsubseteq^\sharp} F^\sharp = \text{lfp}_{\lambda s \bullet \{\perp\}}^{\dot{\sqsubseteq}^{\text{EM}}} F^\sharp$

*Sketch of proof*

- $\text{lfp}_{\lambda s \bullet \{\perp\}}^{\dot{\sqsubseteq}^{\text{EM}}} F^\sharp$  exists since  $F^\sharp$  is Egli-Milner monotonic and  $\langle \wp(\Sigma_\perp) - \{\emptyset\}, \dot{\sqsubseteq}^{\text{EM}} \rangle$  is a cpo;
- $\text{lfp}_{\lambda s \bullet \{\perp\}}^{\dot{\sqsubseteq}^{\text{EM}}} F^\sharp = \text{lfp}_{\lambda s \bullet \{\perp\}}^{\sqsubseteq^\sharp} F^\sharp$  since the iterates exactly coincide.  
□

## Comparing the orderings $\sqsubseteq^\sharp$ and $\dot{\sqsubseteq}^{\text{EM}}$

- The lub  $\sqcup^\sharp$  provides a semantics to the parallel or:

$$[P \parallel Q] = [P] \sqcup^\sharp [Q]$$

(nontermination of  $P \parallel Q$  only if both  $P$  and  $Q$  do not terminate);

- The lub  $\sqcup^{\text{EM}}$  may not be defined.

## Fixpoint Iterates Reordering

- Let  $\langle \langle D, \sqsubseteq, \perp, \sqcup \rangle, F \rangle$  be a fixpoint semantic specification;
- let  $E$  be a set and  $\preceq$  be a binary relation on  $E$ , such that:
  1.  $\preceq$  is a pre-order on  $E$ ;
  2. all iterates  $F^\delta$ ,  $\delta \in \mathbb{O}$  of  $F$  belong to  $E$ ;
  3.  $\perp$  is the  $\preceq$ -infimum of  $E$ ;
  4. the restriction  $F|_E$  of  $F$  to  $E$  is  $\preceq$ -monotone;
  5. for all  $x \in E$ , if  $\lambda$  is a limit ordinal and  $\forall \delta < \lambda : F^\delta \preceq x$  then  $\bigcup_{\delta < \lambda} F^\delta \preceq x$ .
- Then  $\text{lfp}_\perp^{\sqsubseteq} F = \text{lfp}_\perp^{\preceq} F|_E \in E$ .

## Nondeterministic Smyth/Demoniac Denotational Semantics


- $\tau^\# \stackrel{\Delta}{=} \alpha^\#(\tau^\natural)$  where
  - $\alpha^\#(f) \stackrel{\Delta}{=} \lambda s. f(s) \cup \{s' \in \Sigma \mid \perp \in f(s)\};$
  - $\gamma^\#(g) \stackrel{\Delta}{=} g.$
- $\langle \Sigma \longmapsto \wp(\Sigma_\perp), \dot{\subseteq} \rangle \xleftarrow[\alpha^\#]{\gamma^\#} \langle \Sigma \longmapsto (\wp(\Sigma) \cup \{\Sigma_\perp\}), \dot{\subseteq} \rangle.$

© P. Cousot


77

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Examples of Other Possible Demoniac Iterate Orderings



Demoniac ordering  $\sqsubseteq^\#$    Demoniac ordering  $\sqsubseteq^\diamond$



Smyth ordering  $\sqsubseteq^s$    Flat ordering  $\sqsubseteq^w$

© P. Cousot

79

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Demoniac Denotational Semantics in Fixpoint Form

$$\tau^\# = \text{lfp}_{\dot{\perp}^=}^{\dot{\sqsubseteq}^=} F^\natural$$

where:

- $F^\natural \stackrel{\Delta}{=} \lambda s. (\forall s' \in \Sigma : \neg(s \tau s') ? \{s\} \mid \{s' \mid \exists s'' \in \Sigma : s \tau s'' \wedge s' \in f(s'')\})$
- The DCPO<sup>20</sup>  $\langle \dot{D}^=, \dot{\sqsubseteq}^=, \dot{\perp}^=, \dot{\sqcup}^= \rangle$  is the restriction of the pointwise extension of the flat DCPO  $\langle D^=, \sqsubseteq^=, \perp^=, \sqcup^= \rangle$ ;
- $D^= \stackrel{\Delta}{=} (\wp(\Sigma) \setminus \{\emptyset\}) \cup \{\perp^=\}$
- $\perp^= \stackrel{\Delta}{=} \Sigma_\perp$
- $\dot{D}^= \stackrel{\Delta}{=} \{f \in \Sigma \longmapsto D^= \mid \forall s, s' \in \Sigma : (s' \in f(s) \wedge f(s) \neq \perp^=) \Rightarrow (s' \in \check{f} \wedge f(s') = \{s'\})\}.$

This is not the classical Smyth ordering!

<sup>20</sup> Directed Complete Poset.

© P. Cousot

78

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Minimality of $\langle \dot{D}^=, \dot{\sqsubseteq}^= \rangle$

- Let  $\langle E, \preccurlyeq \rangle$  be any poset such that:

- $\dot{\perp}^=$  is the  $\preccurlyeq$ -infimum of  $E$ ,
- $F^\natural[\tau] \stackrel{\Delta}{=} \lambda s. (\forall s' \in \Sigma : \neg(s \tau s') ? \{s\} \mid \{s' \mid \exists s'' \in \Sigma : s \tau s'' \wedge s' \in f(s'')\}) \in E \xrightarrow{\text{mon}} E$  is  $\preccurlyeq$ -monotone, and
- $\forall \tau : \tau^\# = \text{lfp}_{\dot{\perp}^=}^{\dot{\sqsubseteq}^=} F^\natural[\tau]$

then:

- $\dot{D}^= \subseteq E$ , and
- $\dot{\sqsubseteq}^= \subseteq \preccurlyeq$ .

© P. Cousot

80

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Hoare/Angelic Denotational Semantics

- $\tau^\flat \stackrel{\Delta}{=} \dot{\alpha}^\flat(\tau^\natural)$
- $\dot{\alpha}^\flat(\varphi) \stackrel{\Delta}{=} \lambda s \cdot \varphi(s) \cap \Sigma$
- $\dot{\gamma}^\flat(\phi) \stackrel{\Delta}{=} \lambda s \cdot \phi(s) \cup \{\perp\}$
- $\langle \Sigma \longmapsto \wp(\Sigma_\perp), \subseteq \rangle \xleftarrow[\dot{\alpha}^\flat]{\dot{\gamma}^\flat} \langle \Sigma \longmapsto \wp(\Sigma), \subseteq \rangle$
- $\tau^\flat = \text{lfp}_{\emptyset}^{\dot{\subseteq}} F^\natural$  where  $F^\natural = \lambda s \cdot (\forall s' \in \Sigma : \neg(s \tau s') \ ? \ \{s\} \mid \{s' \mid \exists s'' \in \Sigma : s \tau s'' \wedge s' \in f(s'')\})$  is a complete  $\dot{\cup}$ -morphism on the complete lattice  $\langle \Sigma \longmapsto \wp(\Sigma), \subseteq, \emptyset, \lambda s \cdot \Sigma, \dot{\cup}, \dot{\cap} \rangle$  which is the pointwise extension of the powerset  $\langle \wp(\Sigma), \emptyset \rangle$ .

© P. Cousot

81

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## DENOTATIONAL/FUNCTIONAL DETERMINISTIC SEMANTICS

© P. Cousot

82

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Denotational/Functional Deterministic Abstraction

- $\langle \wp(\Sigma_\perp), \subseteq \rangle \xleftarrow[\dot{\alpha}^s]{\dot{\gamma}^s} \langle \Sigma \cup \{\perp, \top\}, \sqsubseteq^s \rangle$  where  $\forall s \in \Sigma : \perp \sqsubseteq^s \perp \sqsubseteq^s$   
 $s \sqsubseteq^s s \sqsubseteq^s \top \sqsubseteq^s \top$

- The abstraction  $\alpha^s$  disregards nondeterminism:

$$\begin{array}{ll} \alpha^s(\emptyset) \stackrel{\Delta}{=} \perp & \gamma^s(\perp) \stackrel{\Delta}{=} \{\perp\} \\ \alpha^s(\{\perp\}) \stackrel{\Delta}{=} \perp & \\ \alpha^s(\{s\}) = \alpha^s(\{s, \perp\}) \stackrel{\Delta}{=} s, s \in \Sigma & \gamma^s(s) \stackrel{\Delta}{=} \{s, \perp\} \\ \alpha^s(X) \stackrel{\Delta}{=} \top, \text{ otherwise} & \gamma^s(\top) \stackrel{\Delta}{=} \Sigma_\perp \end{array}$$

- $\langle \Sigma \longmapsto \wp(\Sigma_\perp), \subseteq \rangle \xleftarrow[\dot{\alpha}^s]{\dot{\gamma}^s} \langle \Sigma \longmapsto (\Sigma \cup \{\perp, \top\}), \dot{\sqsubseteq}^s \rangle$  where  $\dot{\alpha}^s(f) \stackrel{\Delta}{=} \lambda s \cdot \alpha^s(f(s))$  and  $\dot{\gamma}^s(f) \stackrel{\Delta}{=} \lambda s \cdot \gamma^s(f(s))$

© P. Cousot

83

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Natural $\tau^\natural$ and deterministic $\tau^\top$ denotational semantics of nondeterministic transition systems $\tau$

 $\tau^\natural(a) = \{b\}$ $\tau^\top(a) = b$ $\tau^\top(b) = b$ $\tau^\top(c) = b$	 $\tau^\natural(a) = \{b, \perp\}$ $\tau^\top(a) = b$ $\tau^\top(b) = b$ $\tau^\top(c) = \perp$	 $\tau^\natural(a) = \{b, c\}$ $\tau^\top(a) = \top$ $\tau^\top(b) = b$ $\tau^\top(c) = c$
--	---	--

© P. Cousot

84

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Fixpoint Denotational/Functional Deterministic Semantics of a Transition System $\langle \Sigma, \tau \rangle$

- $\tau^s \stackrel{\Delta}{=} \dot{\alpha}^s(\tau^\natural) = \dot{\alpha}^s(\text{lfp}_{\lambda s \bullet \{\perp\}}^{\sqsubseteq^\natural} F^\natural) = \text{lfp}_{\lambda s \bullet \perp}^{\sqsubseteq^s} F^s$
- $F^s \stackrel{\Delta}{=} \lambda f \bullet \lambda s \bullet (\forall s' \in \Sigma : \neg(s \tau s') ? s \mid \sqcup^s \{f(s'') \mid s \tau s''\})$

*Proof*

- $\dot{\alpha}^s(\lambda s \bullet \{\perp\}) = \lambda s \bullet \perp$ ;
- $\dot{\alpha}^s \circ F^d = F^s \circ \dot{\alpha}^s$  leads to the definition of  $F^d$ ;
- $\dot{\alpha}^s(\dot{\sqcup}_i^\infty f_i) = \dot{\sqcup}_i^s \dot{\alpha}^s(f_i)$  leads to the definition of the  $\sqsubseteq^s$ -lub  $\dot{\sqcup}^s$ ;
- $F^s$  is monotonic for  $\sqsubseteq^s$ ;
- Kleene's fixpoint transfer theorem applies.

□

## The Rôle of $\top$

- The top element  $\top$  is often eliminated from Scott's domains by lack of intuitive interpretation;
- We interpret  $\top$  as an abstraction forgetting about nondeterminism.

## Deterministic Transition System, Scott's Semantics

- If  $\tau$  is deterministic, then  $\tau \in \Sigma \mapsto \Sigma$  and

$$F^s = \lambda f \bullet \lambda s \bullet (s \notin \text{dom } \tau ? s \mid \tau(s)) \quad (1)$$

- $\top$  is unreachable and can be eliminated from the domain so that  $\sqsubseteq^s$  is exactly Scott ordering.

## PREDICATE TRANSFORMER SEMANTICS

## Nondeterministic Denotational to Predicate Transformer Abstractions

$$\begin{aligned}
\alpha^{-1} &\stackrel{\Delta}{=} \lambda f \in D \longmapsto \wp(E) \bullet \lambda s' \bullet \{s \mid s' \in f(s)\} \\
\gamma^{-1} &\stackrel{\Delta}{=} \lambda f \in E \longmapsto \wp(D) \bullet \lambda s \bullet \{s' \mid s \in f(s')\} \\
\alpha^{\triangleright} &\stackrel{\Delta}{=} \lambda f \in D \longmapsto \wp(E) \bullet \lambda P \in \wp(D) \bullet \{s' \mid \exists s \in P : s' \in f(s)\} \\
\gamma^{\triangleright} &\stackrel{\Delta}{=} \lambda \Psi \in \wp(D) \longmapsto \wp(E) \bullet \lambda s \bullet \Psi(\{s\}) \\
\alpha^{\cup} &\stackrel{\Delta}{=} \lambda \Psi \in \wp(D) \longmapsto \wp(E) \bullet \lambda Q \in \wp(E) \bullet \{s \mid \Psi(\{s\}) \cap Q \neq \emptyset\} \\
\gamma^{\cup} &\stackrel{\Delta}{=} \lambda \Psi \in \wp(E) \longmapsto \wp(D) \bullet \lambda P \in \wp(D) \bullet \{s' \mid \Psi(\{s'\}) \cap P \neq \emptyset\} \\
\alpha^{\sim} &\stackrel{\Delta}{=} \lambda \Psi \in \wp(D) \longmapsto \wp(E) \bullet \lambda P \in \wp(D) \bullet \neg(\Psi(\neg P)) \\
\gamma^{\sim} &\stackrel{\Delta}{=} \lambda \Psi \in \wp(E) \longmapsto \wp(D) \bullet \lambda P \in \wp(D) \bullet \neg(\Psi(\neg P)) \\
\alpha^{\cap} &\stackrel{\Delta}{=} \lambda \Phi \in \wp(D) \longmapsto \wp(E) \bullet \lambda Q \in \wp(E) \bullet \{s \mid \Phi(\neg\{s\}) \cup Q = E\} \\
\gamma^{\cap} &\stackrel{\Delta}{=} \lambda \Phi \in \wp(E) \longmapsto \wp(D) \bullet \lambda P \in \wp(D) \bullet \{s' \mid \Phi(\neg\{s'\}) \cup P = D\}
\end{aligned}$$

© P. Cousot

89

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Galois Connection Commutative Diagram

$$\begin{array}{ccccc}
\langle D \longmapsto \wp(E), \dot{\subseteq} \rangle & \xleftarrow[\alpha^{\triangleright}]{} & \langle \wp(D) \longmapsto \wp(E), \dot{\subseteq} \rangle & \xleftarrow[\alpha^{\sim}]{} & \langle \wp(D) \longmapsto \wp(E), \dot{\supseteq} \rangle \\
\downarrow \alpha^{-1} & & \downarrow \gamma^{-1} & & \downarrow \alpha^{\cap} \\
\langle E \longmapsto \wp(D), \dot{\subseteq} \rangle & \xleftarrow[\alpha^{\triangleright}]{} & \langle \wp(E) \longmapsto \wp(D), \dot{\subseteq} \rangle & \xleftarrow[\alpha^{\sim}]{} & \langle \wp(E) \longmapsto \wp(D), \dot{\supseteq} \rangle
\end{array}$$

© P. Cousot

90

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Predicate Transformer Abstractions

If  $f \in D \longmapsto \wp(E)$ :

$$\begin{aligned}
\text{gsp}\llbracket f \rrbracket &\stackrel{\Delta}{=} \alpha^{\triangleright}[f] \in \wp(D) \longmapsto \wp(E) \\
&= \lambda P \in \wp(D) \bullet \{s' \in E \mid \exists s \in P : s' \in f(s)\} \\
\text{gspa}\llbracket f \rrbracket &\stackrel{\Delta}{=} \alpha^{\sim} \circ \alpha^{\triangleright}[f] \in \wp(D) \longmapsto \wp(E) \\
&= \lambda P \in \wp(D) \bullet \{s' \in E \mid \forall s \in D : s' \in f(s) \Rightarrow s \in P\} \\
\text{gwp}\llbracket f \rrbracket &\stackrel{\Delta}{=} \alpha^{\sim} \circ \alpha^{\triangleright} \circ \alpha^{-1}[f] \in \wp(E) \longmapsto \wp(D) \\
&= \lambda Q \in \wp(E) \bullet \{s \in D \mid \forall s' \in E : s' \in f(s) \Rightarrow s' \in Q\} \\
\text{gwpa}\llbracket f \rrbracket &\stackrel{\Delta}{=} \alpha^{\triangleright} \circ \alpha^{-1}[f] \in \wp(E) \longmapsto \wp(D) \\
&= \lambda Q \in \wp(E) \bullet \{s \in D \mid \exists s' \in Q : s' \in f(s)\}
\end{aligned}$$

© P. Cousot

91

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Generalized Weakest Precondition Semantics

- $\tau^{\text{gwp}} \stackrel{\Delta}{=} \text{gwp}\llbracket \tau^{\natural} \rrbracket = \text{lfp}_{\perp^{\text{gwp}}} \sqsubseteq^{\text{gwp}} F^{\text{gwp}}$
- $F^{\text{gwp}} \in D^{\text{gwp}} \longmapsto D^{\text{gwp}} \stackrel{\Delta}{=} \lambda \Phi \bullet \lambda Q \bullet (\neg \check{\tau} \cup Q) \dot{\cap} \text{gwp}\llbracket \tau^{\blacktriangleright} \rrbracket \circ \Phi$   
 $= \lambda \Phi \bullet \lambda Q \bullet (Q \cap \check{\tau}) \dot{\cup} \text{wp}\llbracket \tau^{\blacktriangleright} \rrbracket \circ \Phi$   
 is a  $\sqsubseteq^{\text{gwp}}$ -monotone map on the complete lattice  $\langle D^{\text{gwp}}, \sqsubseteq^{\text{gwp}}, \perp^{\text{gwp}}, \sqcup^{\text{gwp}} \rangle$
- $\text{wp}\llbracket f \rrbracket Q \stackrel{\Delta}{=} \{s \in \Sigma \mid \exists s' \in \Sigma : s' \in f(s) \wedge \forall s' \in f(s) : s' \in Q\}$
- $D^{\text{gwp}} \stackrel{\Delta}{=} \wp(\Sigma_{\perp}) \longmapsto \wp(\Sigma)$ ,
- $\Phi \sqsubseteq^{\text{gwp}} \Psi \stackrel{\Delta}{=} \forall Q \subseteq \Sigma : \Psi(Q \cup \{\perp\}) \subseteq \Phi(Q \cup \{\perp\}) \wedge \Phi(\Sigma) \subseteq \Psi(\Sigma)$ ,
- $\perp^{\text{gwp}} = \lambda Q \bullet (\perp \in Q ? \Sigma \mid \emptyset)$
- $\sqcup_{i \in \Delta}^{\text{gwp}} \Psi_i \stackrel{\Delta}{=} \lambda Q \bullet \bigcap_{i \in \Delta} \Psi_i(Q \cup \{\perp\}) \cap (\perp \notin Q ? \bigcup_{i \in \Delta} \Psi_i(\Sigma) \mid \Sigma)$ .

© P. Cousot

92

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Dijkstra's Weakest Conservative Precondition Abstraction

- $\langle D^{\text{gwp}}, \dot{\supseteq} \rangle \xleftarrow[\alpha^{\text{wp}}]{\gamma^{\text{wp}}} \langle D^{\text{wp}}, \dot{\supseteq} \rangle$  where  $D^{\text{wp}} \triangleq \wp(\Sigma) \xrightarrow{\circ} \wp(\Sigma)$ ,  $\alpha^{\text{wp}} \triangleq \lambda \Phi \cdot \Phi|_{\wp(\Sigma)}$  and  $\gamma^{\text{wp}}(\Psi) \triangleq \lambda Q \cdot (\perp \notin Q ? \Psi(Q) | \emptyset)$ ;
- $\tau^{\text{wp}} \triangleq \alpha^{\text{wp}}(\tau^{\text{gwp}}) = \alpha^{\text{wp}}(\text{gwp}[\tau^\sharp])$ ;
- Dijkstra's fixpoint characterization of  $\tau^{\text{wp}}$  is for a given postcondition  $Q$ ;
- If  $Q \subseteq E$  then  $\langle \wp(E) \xrightarrow{\circ} \wp(D), \dot{\supseteq} \rangle \xleftarrow[\alpha^Q]{\gamma^Q} \langle \wp(D), \supseteq \rangle$  where  $\alpha^Q(\Phi) \triangleq \Phi(Q)$  and  $\gamma^Q(P) \triangleq \lambda R \cdot (Q \subseteq R ? P | \emptyset)$ ;

## Dijkstra's Weakest Liberal Precondition Semantics

- $\langle D^{\text{gwp}}, \dot{\supseteq} \rangle \xleftarrow[\alpha^{\text{wlp}}]{\gamma^{\text{wlp}}} \langle D^{\text{wlp}}, \dot{\supseteq} \rangle$  where  $D^{\text{wlp}} \triangleq \wp(\Sigma) \xrightarrow{\circ} \wp(\Sigma)$ ,  $\alpha^{\text{wlp}} \triangleq \lambda \Phi \cdot \lambda Q \cdot \Phi(Q \cup \{\perp\})$  and  $\gamma^{\text{wlp}}(\Psi) \triangleq \lambda Q \cdot (\perp \in Q ? \Psi(Q) | \emptyset)$ ;
- $\tau^{\text{wlp}} \triangleq \alpha^{\text{wlp}}(\tau^{\text{gwp}}) = \text{gwp}[\tau^\flat]$ ;
- By Kleene fixpoint transfer,  $\tau^{\text{wlp}} = \lambda Q \cdot \text{gfp}_\Sigma^\subseteq F^{\text{wp}}[Q]$ .

## Dijkstra's Weakest Conservative Precondition Semantics

From  $\tau^{\text{wp}}(Q) = \alpha^Q(\alpha^{\text{wp}}(\tau^{\text{gwp}}))$  and Kleene fixpoint transfer theorem, we derive:

- $\tau^{\text{wp}}(Q) = \lambda Q \cdot \text{lfp}_\emptyset^\subseteq F^{\text{wp}}[Q]$
  - $F^{\text{wp}} \in \wp(\Sigma) \xrightarrow{\circ} \wp(\Sigma) \xrightarrow{\text{m}} \wp(\Sigma)$
  - $\tau^\blacktriangleright(s) \triangleq \{s' \mid s \tau s'\}$ ;
  - $F^{\text{wp}}[Q] \triangleq \lambda P \cdot (Q \cap \check{\tau}) \cup \text{wp}[\tau^\blacktriangleright] P$   
 $= \lambda P \cdot (\neg \check{\tau} \cup Q) \cap \text{gwp}[\tau^\blacktriangleright] P$
- is a  $\subseteq$ -monotone map on the complete lattice  $\langle \wp(\Sigma), \subseteq, \emptyset, \Sigma, \cup, \cap \rangle$ .

## Correspondence Between Pre- and Postcondition Semantics

If  $f \in D \xrightarrow{\circ} \wp(E)$  then  $\langle \wp(D), \subseteq \rangle \xrightarrow[\text{gsp}[f]]{\text{gwp}[f]} \langle \wp(E), \subseteq \rangle$ .


## AXIOMATIC SEMANTICS

### Galois Connections, Complete Join/Meet Morphisms and Tensor Product

- G. c.:  $\langle D^\sharp, \sqsubseteq^\sharp \rangle \leftrightarrows \langle D^\sharp, \sqsubseteq^\sharp \rangle \stackrel{\Delta}{=} \{(\alpha, \gamma) \mid \langle D^\sharp, \sqsubseteq^\sharp \rangle \xleftarrow[\alpha]{} \langle D^\sharp, \sqsubseteq^\sharp \rangle\}$ ;
- Complete join morphisms:  $D^\sharp \xrightarrow{u} D^\sharp \stackrel{\Delta}{=} \{\alpha \in D^\sharp \xrightarrow{} D^\sharp \mid \forall X \subseteq D^\sharp : \alpha(\sqcup^\sharp X) = \sqcup^\sharp \alpha^\blacktriangleright(X)\}$ ;
- Complete meet morphisms:  $D^\sharp \xrightarrow{n} D^\sharp \stackrel{\Delta}{=} \{\gamma \in D^\sharp \xrightarrow{} D^\sharp \mid \forall Y \subseteq D^\sharp : \gamma(\sqcap^\sharp Y) = \sqcap^\sharp \gamma^\blacktriangleright(Y)\}$ ;
- Tensor products:  $\langle D^\sharp, \sqsubseteq^\sharp \rangle \otimes \langle D^\sharp, \sqsubseteq^\sharp \rangle \stackrel{\Delta}{=} \{H \in \wp(D^\sharp \times D^\sharp) \mid (1) \wedge (2) \wedge (3)\}$  where the conditions are:
  1.  $(X \sqsubseteq^\sharp X' \wedge \langle X', Y' \rangle \in H \wedge Y' \sqsubseteq^\sharp Y) \Rightarrow (\langle X, Y \rangle \in H)$ ;
  2.  $(\forall i \in \Delta : \langle X_i, Y \rangle \in H) \Rightarrow (\langle \sqcup_{i \in \Delta}^\sharp X_i, Y \rangle \in H)$ ;
  3.  $(\forall i \in \Delta : \langle X, Y_i \rangle \in H) \Rightarrow (\langle X, \sqcap_{i \in \Delta}^\sharp Y_i \rangle \in H)$ .

### Galois Connection Commutative Diagram

$$\begin{aligned} 1((\alpha, \gamma)) &\stackrel{\Delta}{=} \alpha & \text{HA}(\alpha) &\stackrel{\Delta}{=} \{(\langle x, y \rangle \in D^\sharp \times D^\sharp \mid \alpha(x) \sqsubseteq^\sharp y)\} \\ 2((\alpha, \gamma)) &\stackrel{\Delta}{=} \gamma & \text{HC}(\gamma) &\stackrel{\Delta}{=} \{(\langle x, y \rangle \in D^\sharp \times D^\sharp \mid x \sqsubseteq^\sharp \gamma(y))\} \\ \text{AC}(\gamma) &\stackrel{\Delta}{=} \lambda x \cdot \sqcap^\sharp \{y \mid x \sqsubseteq^\sharp \gamma(y)\} & \text{AH}(H) &\stackrel{\Delta}{=} \lambda x \cdot \sqcap^\sharp \{y \mid \langle x, y \rangle \in H\} \\ \text{CA}(\alpha) &\stackrel{\Delta}{=} \lambda y \cdot \sqcup^\sharp \{x \mid \alpha(x) \sqsubseteq^\sharp y\} & \text{CH}(H) &\stackrel{\Delta}{=} \lambda y \cdot \sqcup^\sharp \{x \mid \langle x, y \rangle \in H\} \end{aligned}$$



### Floyd/Hoare/Naur Partial Correctness Semantics

- $\tau^{\text{pH}} \stackrel{\Delta}{=} \text{HC}(\tau^{\text{wlp}})$ ;
- $\tau^{\text{pH}} = \{\langle P, Q \rangle \in \wp(\Sigma) \otimes \wp(\Sigma) \mid \exists I \in \wp(\Sigma) : P \subseteq I \wedge I \subseteq \text{gwp}[\tau^\blacktriangleright] I \wedge (I \cap \check{\tau}) \subseteq Q\}$ .

*Proof* By Park fixpoint induction: if  $\langle D, \sqsubseteq, \perp, \top, \sqcup, \sqcap \rangle$  is a complete lattice,  $F \in D \xrightarrow{m} D$  is  $\sqsubseteq$ -monotone and  $L \in D$  then  $\text{lfp}_\perp^\sqsubseteq F \sqsubseteq P \iff (\exists I : F(I) \sqsubseteq I \wedge I \sqsubseteq P)$ .  $\square$

## Hoare Logic

- Hoare triples:  $\{P\}\tau^{\vec{\omega}}\{Q\} \triangleq \langle P, Q \rangle \in \tau^{\text{ph}}$ ,  $\{P\}\tau\{Q\} \triangleq P \subseteq \text{gwp}[\tau^\blacktriangleright]Q$ ;
- Hoare logic:  $\{P\}\tau^{\vec{\omega}}\{Q\}$  if and only if it derives from the axiom:

$$\{\text{gwp}[\tau^\blacktriangleright]Q\}\tau\{Q\} \quad (\tau)$$

and the following inference rules:

$$\frac{P \subseteq P', \{P'\}\tau^{\vec{\omega}}\{Q'\}, Q' \subseteq Q}{\{P\}\tau^{\vec{\omega}}\{Q\}} (\Rightarrow) \quad \frac{\{P_i\}\tau^{\vec{\omega}}\{Q\}, i \in \Delta}{\left\{ \bigcup_{i \in \Delta} P_i \right\} \tau^{\vec{\omega}}\{Q\}} (\vee)$$

$$\frac{\{P\}\tau^{\vec{\omega}}\{Q_i\}, i \in \Delta}{\{P\}\tau^{\vec{\omega}}\left\{ \bigcap_{i \in \Delta} Q_i \right\}} (\wedge) \quad \frac{\frac{\{I\}\tau\{I\}}{\{I\}\tau^{\vec{\omega}}\{I \cap \check{\tau}\}} (\tau^{\vec{\omega}})}{(\tau^{\vec{\omega}})}$$

## Manna/Pnueli Total Correctness Logic

- Manna/Pnueli triples:  $[P]\tau^{\vec{\omega}}[Q] \triangleq \langle P, Q \rangle \in \tau^{\text{th}}$ ,  $[P]\tau[Q] \triangleq P \subseteq \text{gwp}[\tau^\blacktriangleright]Q$ ;
- Manna/Pnueli total correctness axiomatic semantics:  $[P]\tau^{\vec{\omega}}[Q]$  if and only if it derives from the axiom  $(\tau)$ , the inference rules  $(\Rightarrow)$ ,  $(\wedge)$ ,  $(\vee)$  and the following:

$$\frac{I^0 \subseteq Q \cap \check{\tau}, \bigwedge_{\delta=1}^{\epsilon} I^\delta \subseteq \neg \check{\tau} \cup Q, \bigwedge_{\delta=1}^{\epsilon} [I^\delta]\tau[\bigcup_{\beta < \delta} I^\beta]}{[I^\epsilon]\tau^{\vec{\omega}}[Q]} (\tau^{\vec{\omega}})$$

## Floyd Total Correctness Semantics

- $\tau^{\text{th}} \triangleq \text{HC}(\tau^{\text{wp}})$ ;
- $\tau^{\text{th}} = \{\langle P, Q \rangle \in \wp(\Sigma) \otimes \wp(\Sigma) \mid \exists \epsilon \in \mathbb{O} : \exists I \in (\epsilon + 1) \longmapsto \wp(\Sigma) : \forall \delta \leq \epsilon : I^\delta \subseteq (\neg \check{\tau} \cup Q) \cap \text{gwp}[\tau^\blacktriangleright]\left(\bigcup_{\beta < \delta} I^\beta\right) \wedge P \subseteq I^\epsilon\}$ .
- Floyd (equivalent) verification conditions:

$$\forall s \in I^\delta : \bigvee \forall s' : \neg(s \tau s') \wedge s \in Q \\ \exists s' : s \tau s' \wedge \forall s' : s \tau s' \Rightarrow (\exists \beta < \delta : s' \in I^\beta)$$

*Proof* By the lower fixpoint induction principle: if  $\langle D, \sqsubseteq, \perp, \sqcup \rangle$  is a DCPO,  $F \in D \xrightarrow{\text{m}} D$  is  $\sqsubseteq$ -monotone,  $\perp \in D$  satisfies  $\perp \sqsubseteq F(\perp)$  and  $P \in D$  then  $P \sqsubseteq \text{lfp}_\perp F \iff (\exists \epsilon \in \mathbb{O} : \exists I \in (\epsilon + 1) \longmapsto D : I^0 \sqsubseteq \perp \wedge \forall \delta : 0 < \delta \leq \epsilon \Rightarrow I^\delta \sqsubseteq F(\bigcup_{\zeta < \delta} I^\zeta) \wedge P \sqsubseteq I^\epsilon)$ .  $\square$

## LATTICE OF SEMANTICS

## Comparison of Semantics

- $\tau^\sharp \in D^\sharp \leq \tau^\sharp \in D^\sharp$  iff  $\tau^\sharp = \alpha^\sharp(\tau^\sharp)$  and  $\langle D^\sharp, \leq \rangle \xrightarrow[\alpha^\sharp]{\gamma^\sharp} \langle D^\sharp, \leq \rangle$  is a preorder between semantics;
- The quotient poset is isomorphic to Ward lattice of upper closure operators  $\gamma^\sharp \circ \alpha^\sharp$  on  $\langle D^\infty, \subseteq \rangle$ ;
- We get a lattice of semantics which is part of the lattice of abstract interpretations.

© P. Cousot

105

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997


## APPLICATION TO THE (EAGER) LAMBDA-CALCULUS (PROSPECTIVE)

© P. Cousot

107

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Lattice of Semantics



© P. Cousot

106

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Relational Semantics with Closures

$$E \vdash \lambda x \cdot e \Rightarrow \langle x, e, E \rangle$$

$$\frac{E \vdash e_1 \Rightarrow \perp}{E \vdash e_1(e_2) \Rightarrow \perp}$$

$$\frac{c = \langle x, e, E[f \leftarrow c] \rangle}{E \vdash \mu f \cdot \lambda x \cdot e \Rightarrow c}$$

$$\frac{\begin{array}{l} E \vdash e_1 \Rightarrow \langle x', e', E' \rangle \\ E \vdash e_2 \Rightarrow v, v \neq \Omega \\ E'[x' \leftarrow v] \vdash e' \Rightarrow r \end{array}}{E \vdash e_1(e_2) \Rightarrow r}$$

$$\frac{\begin{array}{l} E \vdash e_1 \Rightarrow \langle x', e', E' \rangle \\ E \vdash e_2 \Rightarrow v, v \neq \Omega \\ E'[x' \leftarrow v] \vdash e' \Rightarrow \perp \end{array}}{E \vdash e_1(e_2) \Rightarrow \perp}$$

© P. Cousot

108

MPI-Kolloquium, Max-Planck-Institut für Informatik, Saarbrücken, 2. Juni 1997

## Denotational Semantics

$$u, f, \varphi \in U \cong \{\Omega\}_{\perp}^{\top} \oplus \mathbb{Z}_{\perp}^{\top} \oplus [U \longrightarrow U]_{\perp}^{\top} \text{ values}$$

$$R \in \mathbb{R} \triangleq X \longrightarrow U \quad \text{environments}$$

$$\phi \in S \triangleq R \longrightarrow U \quad \text{semantic domain}$$

$$S[\lambda x \cdot e]R \triangleq \begin{cases} \lambda u \cdot (u = \perp ? \perp \\ | u = \Omega ? \Omega \\ | S[e]R[x \leftarrow u]) \end{cases}$$

$$S[e_1(e_2)]R \triangleq \begin{cases} (S[e_1]R = \perp \vee S[e_2]R = \perp) ? \perp \\ | S[e_1]R = f \in [U \longrightarrow U] ? f(S[e_2]R) \\ | \Omega \end{cases}$$

$$S[\mu f \cdot \lambda x \cdot e]R \triangleq \text{lfp } \sqsubseteq \lambda \varphi \cdot S[\lambda x \cdot e]R[f \leftarrow \varphi]$$

- $\alpha \in (\mathbb{X} \longrightarrow V) \longrightarrow (\mathbb{X} \longrightarrow U)$ :

$$\alpha(E) \triangleq \lambda x \cdot \alpha(E(x))$$

- $\alpha \in \wp((\mathbb{X} \longrightarrow V) \times V) \longrightarrow ((\mathbb{X} \longrightarrow U) \longrightarrow U)$ :

$$\alpha(\Phi[e]) \triangleq \lambda R \cdot \alpha(\{r \mid \exists E : \alpha(E) = R \wedge E \vdash e \Rightarrow r \in \Phi[e]\})$$

## Abstraction

- The rules of the relational semantics can be interpreted as least fixpoints for the bifinite ordering;
- The abstraction function  $\alpha \in \wp(V) \longrightarrow U$  is as follows<sup>21</sup>:

$$\alpha(\emptyset) \triangleq \perp$$

$$\alpha(\{\perp\}) \triangleq \perp$$

$$\alpha(\{z\}) = \alpha(\{z, \perp\}) \triangleq z, \quad z \in \mathbb{Z}$$

$$\alpha(\{\Omega\}) \triangleq \Omega$$

$$\alpha(X) \triangleq \top, \quad \text{otherwise.}$$

$$\alpha(\langle x, e, E \rangle) \triangleq \lambda u \in U \cdot \alpha(\{r \mid \exists v \in V : \alpha(\{v\}) = u \wedge E[x \leftarrow v] \vdash e \Rightarrow r\})$$

<sup>21</sup> Liftings and injections are omitted.

## Alternative Partitionning of Executions

- We have explored linear time (set of traces) semantics with partition between finite and infinite traces;
- A different partitionning for branching time (tree) semantics would be states with or without later possibility to branch toward a nonterminating execution.

## Need for semantics at various levels of refinement

- Many semantics at different levels of abstraction are needed for program analysis;
- A unified framework for presenting all these semantics seems indispensable.

## Further Work for Semantics

- Consider realistic practical languages ( $C^{++}$ , Java, ML, etc);
- Consider computable approximations of semantic domains (to be used in program analysis);
- A need for mathematical foundations but also applications of programming semantics;
- A lot of work for future applied semanticicians (like applied mathematicians).